



F21 Transmitter (only) Two Speed

Key features

- Two-Speed Functionality: Enables adjustable speed settings for optimal control during operation.
- User-Friendly Interface: Intuitive layout with clearly labeled buttons for easy operation.
- Durable Design: Built to withstand tough industrial conditions for long-lasting performance.
- 3 Year Warranty, Customer Support and Service in the USA

F21 Transmitter (only) Two Speed Description

The F21 Transmitter (Only) is a robust and reliable remote control designed for seamless operation of various industrial applications. Featuring a two-speed functionality, this transmitter allows for precise control over equipment, enhancing both safety and efficiency. Its user-friendly design and durable construction make it ideal for demanding environments.

Technical Specifications

FCC ID	OFNF21	Transmitter Power	≤10dBm
Transmitter Power Supply	2 AA batteries	Wireless Frequency Range	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	IEC Motor Protection	IP65
Control Distance	Approx 60m (100 meters is customized)	Operating Temperature Range	-40 ~ 185 °F / -40 ~ 85°C
Safety Code	32 bits (4.3 billion)	Warranty	3 Year

F21-2S/2D TRANSMITTER

Small, economical, convenient



MODEL: F21-2S-TX
ITEM CODE: 921-002-001
Dimensions: 132 x 45 x 28 mm
Weight: 98g (without batteries)

Product Features:

- Two single/double speed buttons, one "STOP"
- 6 control contactors.
- With battery voltage warning device, the power supply is cut off during low power
- Safety key switch to prevent from unauthorized user.
- Program the button function by computer interface.
- Up/Down can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna.
- Operation and maintenance manual.

Safety features:

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



Unit Weight & Dimensions

Total Unit Weight 1 lbs / 1 Kg

Packaging Weight & Dimensions

Package 1 Net Weight 1 lbs / 0 Kg

Package 1 Width 2 in / 5.08 cm

Package 1 Gross Weight 1 lbs / 0 Kg

Package 1 Height 5 in / 12.7 cm

Package 1 Length 2 in / 5.08 cm