



F21 Transmitter (only) Single Speed

Key features

- Single-Speed Operation: Simplified control for consistent and straightforward equipment handling.
- User-Friendly Interface: Clearly labeled buttons for easy operation and quick access.
- Durable Construction: Built to withstand tough industrial conditions for long-lasting performance.
- 3 Year Warranty, Customer Support and Service in the USA

F21 Transmitter (only) Single Speed

The F21 Transmitter (Only) is a reliable remote control designed for efficient operation of various industrial applications. Featuring single-speed functionality, this transmitter provides straightforward control for lifting and moving equipment, enhancing safety and ease of use. Its robust design ensures durability, making it suitable for demanding environments.

Technical Specifications

FCC ID	OFNF21	Transmitter Power	≤10dBm
Transmitter Power Supply	2 AA batteries	Wireless Frequency Range	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	IEC Motor Protection	IP65
Control Distance	Approx 60m (100 meters is customized)	Operating Temperature Range	-40 ~ 185 °F / -40 ~ 85°C
Safety Code	32 bits (4.3 billion)	Warranty	3 Year

F21-2S/2D TRANSMITTER

Small, economical, convenient



MODEL: F21-2S-TX
ITEM CODE: 921-002-001
Dimensions: 132 x 45 x 28 mm
Weight: 98g (without batteries)

Product Features:

- Two single/double speed buttons, one "STOP"
- 6 control contactors.
- With battery voltage warning device, the power supply is cut off during low power
- Safety key switch to prevent from unauthorized user.
- Program the button function by computer interface.
- Up/Down can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna.
- Operation and maintenance manual.

Safety features:

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



Unit Weight & Dimensions

Total Unit Weight	1 lbs / 1 Kg
Package 1 Net Weight	1 lbs / 0 Kg
Package 1 Width	4 in / 10.16 cm
Package 1 Gross Weight	1 lbs / 0 Kg
Package 1 Height	4 in / 10.16 cm
Package 1 Length	9 in / 22.86 cm

Packaging Weight & Dimensions