



## 2 Channels Telecontrol PWA Series Transmitter

### Key features

- Dual Channel Control: Operate two separate devices independently for enhanced versatility and efficiency.
- User-Friendly Interface: Intuitive layout with clearly labeled buttons for easy operation and quick access.
- Durable Construction: Built to withstand tough conditions, ensuring long-lasting performance in various environments.
- 3 Year Warranty, Customer Support and Service in the USA

### 2 Channels Telecontrol

The 2 Channels Telecontrol PWA Series Transmitter is a versatile remote control solution designed for efficient operation of various equipment. With dual-channel functionality, this transmitter allows users to manage two independent devices seamlessly. Its robust construction and intuitive design make it suitable for a wide range of applications in both industrial and residential settings.

## Technical Specifications

<b>FCC ID</b>	OFNF21	<b>Transmitter Power</b>	≤10dBm
<b>Transmitter Power Supply</b>	2 AA batteries	<b>Wireless Frequency Range</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
<b>Material</b>	Glass-Fiber PA	<b>IEC Motor Protection</b>	IP65
<b>Control Distance</b>	Approx 60m (100 meters is customized)	<b>Operating Temperature Range</b>	-40 ~ 185 °F / -40 ~ 85°C
<b>Safety Code</b>	32 bits (4.3 billion)	<b>Warranty</b>	3 Year

## Unit Weight & Dimensions

<b>Total Unit Weight</b>	0.4 lbs / 1 Kg
--------------------------	----------------

## Packaging Weight & Dimensions

<b>Package 1 Net Weight</b>	0.4 lbs / 0 Kg
<b>Package 1 Width</b>	5 in / 12.7 cm
<b>Package 1 Gross Weight</b>	0.5 lbs / 0 Kg
<b>Package 1 Height</b>	5 in / 12.7 cm
<b>Package 1 Length</b>	5 in / 12.7 cm