



F21 Transmitter (only) 4 Buttons Two Speed

# **F21 Transmitter (only) 4 Buttons Two Speed**

### **Key features**

• 3 Year Warranty, Customer Support and Service in the USA





## **Technical Specifications**

FCC ID	2AZMK-Q1212	Transmitter Power	≤10dBm
Transmitter Power Supply	2 AA batteries	Wireless Frequency Range	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	IEC Motor Protection	IP65
Control Distance	Approx 100m (200 meters is customized)	Operating Temperature Range	-40 ~ 185 °F / -40 ~ 85°C
Safety Code	32 bits (4.3 billion)	Warranty	3 Year



Systems ISO 9001



## F21-4S/4D TRANSMITTER

Economical, safe, convenient





MODEL: F21-4S-TX ITEM CODE: 921-004-001 Dimensions: 156 x 61 x 51 mm Weight: 255g (without batteries)

#### **Product Features:**

- 4 buttons (D means double steps). spare button
- 8 control contactors.
- With battery voltage warning device, the power supply is cut off during low power.
- Program the button function by computer interface.
- Up/Down, East/West can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

#### **Standard Configuration:**

- One transmitter (with hanging belt)
- · One dust bag
- One receiver
- Receiver with 1.6 meter cable
- · Battery: One pair
- · One receiver antenna.
- Operation and maintenance manual.

#### Safety features:

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.

**Packaging Weight & Dimensions** 





## **Unit Weight & Dimensions**

Total Unit Weight	1 lbs / 1 Kg	Package 1 Net Weight	1 lbs / 0 Kg
		Package 1 Width	4 in / 10.16 cm
		Package 1 Gross Weight	1 lbs / 0 Kg
		Package 1 Height	4 in / 10.16 cm



Package 1 Length

9 in / 22.86 cm

