



## F21 Transmitter (only) 4 Buttons Two Speed

### Key features

- Four Button Control: Easily manage multiple functions with intuitive button layout.
- Two-Speed Operation: Adjustable speed settings for precise control during lifting or movement.
- Durable Design: Built to withstand tough conditions, ensuring long-lasting reliability.
- 3 Year Warranty, Customer Support and Service in the USA

### F21 Transmitter

The F21 Transmitter (Only) with 4 Buttons and Two-Speed functionality is a reliable remote control designed for efficient operation of various equipment. This compact transmitter allows for precise control with its two-speed settings, making it ideal for applications that require both speed and accuracy. Its durable construction ensures performance in demanding environments.

## Technical Specifications

<b>FCC ID</b>	2AZMK-Q1212	<b>Transmitter Power</b>	≤10dBm
<b>Transmitter Power Supply</b>	2 AA batteries	<b>Wireless Frequency Range</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
<b>Material</b>	Glass-Fiber PA	<b>IEC Motor Protection</b>	IP65
<b>Control Distance</b>	Approx 100m (200 meters is customized)	<b>Operating Temperature Range</b>	-40 ~ 185 °F / -40 ~ 85°C
<b>Safety Code</b>	32 bits (4.3 billion)	<b>Warranty</b>	3 Year

# F21-4S/4D TRANSMITTER

Economical, safe, convenient



**MODEL:** F21-4S-TX  
**ITEM CODE:** 921-004-001  
**Dimensions:** 156 x 61 x 51 mm  
**Weight:** 255g (without batteries)

**Product Features:**

- 4 buttons (D means double steps). spare button
- 8 control contactors.
- With battery voltage warning device, the power supply is cut off during low power.
- Program the button function by computer interface.
- Up/Down, East/West can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

**Standard Configuration:**

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna.
- Operation and maintenance manual.

**Safety features:**

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



## Unit Weight & Dimensions

**Total Unit Weight** 1 lbs / 1 Kg

## Packaging Weight & Dimensions

**Package 1 Net Weight** 1 lbs / 0 Kg

**Package 1 Width** 4 in / 10.16 cm

**Package 1 Gross Weight** 1 lbs / 0 Kg

**Package 1 Height** 4 in / 10.16 cm

**Package 1 Length**

9 in / 22.86 cm