



## 4 Channel Wireless Remote Control Multi voltage 100~440V

### Key features

- Multi-Voltage Compatibility: Operates within a voltage range of 100V to 440V, suitable for various hoist systems.
- Four Channel Control: Manage up to four separate functions simultaneously for greater flexibility and efficiency.
- Robust and Durable Design: Built to withstand harsh industrial environments, ensuring long-lasting performance.
- 1 Year Warranty, Customer Support and Service in the USA

### Telecontrol Wireless Remote Control

The Wireless Remote Control 4 Channel Radio Remote Control is an advanced and efficient solution designed for seamless operation of hoisting equipment. This remote control system features four independent channels, allowing for versatile management of multiple functions. Its multi-voltage compatibility (100V to 440V) ensures adaptability to a wide range of industrial applications, enhancing both safety and operational efficiency.

## Technical Specifications

<b>FCC Cert ID</b>	OFNF21	<b>Transmitter Power</b>	≤10dBm
<b>Transmitter Power Supply</b>	2 AA batteries	<b>Wireless Frequency Range</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
<b>Material</b>	Glass-Fiber PA	<b>Emergency Stop</b>	Yes
<b>Control Range</b>	300 ft up to 600 ft with optional antenna	<b>Operating Temperature Range</b>	-40 ~ 185 °F / -40 ~ 85°C
<b>Safety Code</b>	32 bits (4.3 billion)	<b>Warranty</b>	1 Year

## F21-4S/4D TRANSMITTER

Economical, safe, convenient



**MODEL:** F21-4S-TX  
**ITEM CODE:** 921-004-001  
**Dimensions:** 156 x 61 x 51 mm  
**Weight:** 255g (without batteries)

**Product Features:**

- 4 buttons (D means double steps). spare button
- 8 control contactors.
- With battery voltage warning device, the power supply is cut off during low power.
- Program the button function by computer interface.
- Up/Down, East/West can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

**Standard Configuration:**

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna.
- Operation and maintenance manual.

**Safety features:**

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



### Unit Weight & Dimensions

**Total Unit Weight** 2 lbs / 1 Kg

### Packaging Weight & Dimensions

**Package 1 Net Weight** 2 lbs / 1 Kg

**Package 1 Width** 13 in / 33.02 cm

**Package 1 Gross Weight** 2 lbs / 1 Kg

**Package 1 Height** 6.5 in / 16.51 cm

**Package 1 Length**

8 in / 20.32 cm