



F21 Transmitter (only) 4 Buttons Single Speed Serie "E"

Key features

- Four Button Layout: Easily manage multiple functions with an intuitive design for quick access.
- Single Speed Operation: Provides reliable and consistent control for effective equipment handling.
- Durable Build: Designed to withstand tough conditions, ensuring long-lasting performance.
- 3 Year Warranty, Customer Support and Service in the USA

F21 Transmitter

The F21 Transmitter (Only) with 4 Buttons and Single Speed functionality is a compact and reliable remote control designed for efficient operation of various equipment. Featuring a straightforward single-speed setting, this transmitter is ideal for applications requiring consistent and reliable control. Its durable construction ensures dependable performance in demanding environments.

Technical Specifications

FCC ID	2AZMK-Q1212	Transmitter Power	≤10dBm
Transmitter Power Supply	2 AA batteries	Wireless Frequency Range	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	IEC Motor Protection	IP65
Control Distance	Approx 100m (200 meters is customized)	Operating Temperature Range	-40 ~ 185 °F / -40 ~ 85°C
Safety Code	32 bits (4.3 billion)	Warranty	3 Year

F21-4S/4D TRANSMITTER Economical, safe, convenient



MODEL: F21-4S-TX
ITEM CODE: 921-004-001
Dimensions: 156 x 61 x 51 mm
Weight: 255g (without batteries)

Product Features:

- 4 buttons (D means double steps). spare button
- 8 control contactors.
- With battery voltage warning device, the power supply is cut off during low power.
- Program the button function by computer interface.
- Up/Down, East/West can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna.
- Operation and maintenance manual.

Safety features:

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



Unit Weight & Dimensions

Total Unit Weight 1 lbs / 1 Kg

Packaging Weight & Dimensions

Package 1 Net Weight 1 lbs / 0 Kg

Package 1 Width 4 in / 10.16 cm

Package 1 Gross Weight 1 lbs / 0 Kg

Package 1 Height 4 in / 10.16 cm

Package 1 Length

9 in / 22.86 cm