# Prol/INCH



			Motor Voltage	
HP	(kW)	208 to 230 V Part Number	400 to 480 V Part Number	480 to 600 V Part Number
0.33 - 0.5	(0.25-0.37)	EZXDB3712A1	EZXDB3714A1	N/A
1 - 1.5	(0.75 - 1.1)	EZXDB1122A1	EZXDB1124A1	EZXDB1126A1
2 - 3	(1.5 - 2.2)	EZXDB2222A1	EZXDB2224A1	EZXDB2226A1
5	(4)	EZXDB4022A1	EZXDB4024A1	EZXDB4026A1
7.5	(5.5)	EZXDB5522A1	EZXDB5524A1	EZXDB5526A1
10	(7.5)	EZXDB7522A1	EZXDB7524A1	EZXDB7526A1
Dynamic B	raking Modu	es without Bui	It-in Resistors	
15 - 20	(11 - 15)	EZXDC1532A1	N/A	N/A
15 - 30	(11 - 22)	N/A	EZXDC2234A1	EZXDC2236A1
Dpen Dyna	mic Braking	<b>Resistors with</b>	mounting brack	kets
15 - 20	(11 - 15)	841-009	841-009	841-010
25 - 30	(18.5 - 22)	N/A	841-011	841-012



### **Key features**

- Compatibility: Specifically designed for use with the EZXDC22234A1 dynamic braking system
- Voltage Range: Operates within a voltage range of 380-480V, ensuring effective application in various industrial setups
- Dynamic Braking Support: Enhances braking performance, allowing for smoother and more controlled deceleration of motors
- 1 Year Warranty, Customer Support and Service in the USA

#### 841-011 Resistor for Dynamic Brake Description

841-011 Resistor is designed for use with dynamic braking systems, specifically compatible with the EZXDC22234A1 model. Operating within a voltage range of 380-480V, this resistor is ideal for enhancing the performance of the PWG7 drive, providing efficient braking capabilities and improved energy management.

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com





## **Technical Specifications**

Warranty

1 Year

# **Unit Weight & Dimensions**

**Total Unit Weight** 

6 lbs / 3 Kg

# **Packaging Weight & Dimensions**

Package 1 Net Weight	6 lbs / 3 Kg
Package 1 Width	9 in / 22.86 cm
Package 1 Gross Weight	8 lbs / 4 Kg
Package 1 Height	9 in / 22.86 cm
Package 1 Length	9 in / 22.86 cm

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com

