





Dynamic Braking Modules with Built-in Resistors

		Motor Voltage			
		208 to 230 V	400 to 480 V	480 to 600 V	
HP	(kW)	Part Number	Part Number	Part Number	
0.33 - 0.5	(0.25-0.37)	EZXDB3712A1	EZXDB3714A1	N/A	
1 - 1.5	(0.75 - 1.1)	EZXDB1122A1	EZXDB1124A1	EZXDB1126A1	
2 - 3	(1.5 - 2.2)	EZXDB2222A1	EZXDB2224A1	EZXDB2226A1	
5	(4)	EZXDB4022A1	EZXDB4024A1	EZXDB4026A1	
7.5	(5.5)	EZXDB5522A1	EZXDB5524A1	EZXDB5526A1	
10	(7.5)	EZXDB7522A1	EZXDB7524A1	EZXDB7526A1	
Dynamic Braking Modules without Built-in Resistors					
15 - 20	(11 - 15)	EZXDC1532A1	N/A	N/A	
15 - 30	(11 - 22)	N/A	EZXDC2234A1	EZXDC2236A1	
Open Dynamic Braking Resistors with mounting brackets					
15 - 20	(11 - 15)	841-009	841-009	841-010	
25 - 30	(18.5 - 22)	N/A	841-011	841-012	



841-012 Resistor for Dynamic Brake EZXDC22236A1 (NOT INCLUDED) 480-600V for PWG7700i and PWK4300i

Key features

- Compatibility: Designed for use with the EZXDC22236A1 dynamic braking system
- Voltage Range: Operates within a voltage range of 480-600V, making it suitable for high-voltage applications
- Dynamic Braking Support: Improves braking performance, allowing for smoother and more controlled motor deceleration
- 1 Year Warranty, Customer Support and Service in the USA

841-012 Resistor for Dynamic Brake Description

841-012 Resistor is specifically designed for dynamic braking applications, compatible with the EZXDC22236A1 model. Operating within a voltage range of 480-600V, this resistor enhances the performance of the PWG7 drive, providing effective braking solutions and improved energy efficiency in industrial settings.





Technical Specifications

Warranty 1 Year

Unit Weight & Dimensions

Packaging Weight & Dimensions

Total Unit Weight	6 lbs / 3 Kg	Package 1 Net Weight	6 lbs / 3 Kg
		Package 1 Width	9 in / 22.86 cm
		Package 1 Gross Weight	8 lbs / 4 Kg
		Package 1 Height	9 in / 22.86 cm
		Package 1 Length	9 in / 22.86 cm

