





Dynamic Braking Modules with Built-in Resistors

HP	(kW)	208 to 230 V Part Number	400 to 480 V Part Number	480 to 600 V Part Number	
0.33 - 0.5	(0.25-0.37)	EZXDB3712A1	EZXDB3714A1	N/A	
1 - 1.5	(0.75 - 1.1)	EZXDB1122A1	EZXDB1124A1	EZXDB1126A1	
2 - 3	(1.5 - 2.2)	EZXDB2222A1	EZXDB2224A1	EZXDB2226A1	
5	(4)	EZXDB4022A1	EZXDB4024A1	EZXDB4026A1	
7.5	(5.5)	EZXDB5522A1	EZXDB5524A1	EZXDB5526A1	
10	(7.5)	EZXDB7522A1	EZXDB7524A1	EZXDB7526A1	
Dynamic Braking Modules without Built-in Resistors					
15 - 20	(11 - 15)	EZXDC1532A1	N/A	N/A	
15 - 30	(11 - 22)	N/A	EZXDC2234A1	EZXDC2236A1	
Open Dynamic Braking Resistors with mounting brackets					
15 - 20	(11 - 15)	841-009	841-009	841-010	
25 - 30	(18.5 - 22)	N/A	841-011	841-012	



EZXDB2224A1 Dynamic Brake with Built-in Resistor 380-480V for PWK625i

Key features

- Built-in Resistor: Features an integrated resistor, simplifying installation and reducing the need for additional components.
- Dynamic Braking Capability: Provides rapid deceleration, enhancing control and responsiveness in various applications.
- Voltage Compatibility: Operates efficiently within a 380-480V range, suitable for standard industrial power systems.
- 1 Year Warranty, Customer Support and Service in the USA

EZXDB2224A1 Dynamic Brake with Built-in Resistor Description

The EZXDB2224A1 Dynamic Brake with Built-in Resistor is designed for the PWK625i series, operating at 380-480V. This dynamic brake module enhances motor control by efficiently dissipating energy during deceleration, preventing overspeed conditions and improving overall operational safety.





Technical Specifications

Warranty 1 Year

Unit Weight & Dimensions

Packaging Weight & Dimensions

Total Unit Weight	4 lbs / 2 Kg	Package 1 Net Weight	4 lbs / 2 Kg
		Package 1 Width	7 in / 17.78 cm
		Package 1 Gross Weight	4 lbs / 2 Kg
		Package 1 Height	7 in / 17.78 cm
		Package 1 Length	7 in / 17.78 cm

