



Radio Remote Control - Wireless Two Channel Transmitter - MultiVoltage Range Remote Control

Key features

- Two Channel Operation: Control two devices at once, enhancing flexibility and efficiency in your operations.
- Multi-Voltage Compatibility: Designed to work with various voltage ranges, accommodating a wide array of equipment.
- Durable Construction: Built to withstand harsh industrial conditions, ensuring long-lasting performance and reliability.
- 3 Year Warranty, Customer Support and Service in the USA

Radio Remote Control Description

The Wireless Two Channel Transmitter is designed for reliable control of industrial equipment, providing versatile operation across multiple voltage levels. This remote control allows for efficient management of two channels simultaneously, making it an essential tool for various applications in demanding environments.

Technical Specifications

FCC ID	2AZMK-Q1212	Safety Code	200 Millions
Buttons	2	Transmitter Power	≤10dBm
Transmitter Power Supply	2 AA batteries	Wireless Frequency Range	433/480 MHz
Material	PA6 30% GF	IEC Motor Protection	IP65
Receiver Power Supply	AC/DC110V-480V	Emergency Stop	YES
Receiver Sensitivity	dBm -112	Operating Temperature Range	-40 ~ 185 °F / -40 ~ 85°C
Control Distance	300 ft / 100 mt	Warranty	3 Year

Unit Weight & Dimensions

A Total Height	5.3"
W Width	2.7"
D Depth	1.2"
Total Unit Weight	5 lbs / 3 Kg

Packaging Weight & Dimensions

Package 1 Net Weight	5 lbs / 2 Kg
Package 1 Width	10 in / 25.4 cm
Package 1 Gross Weight	4 lbs / 2 Kg
Package 1 Height	4 in / 10.16 cm
Package 1 Length	12 in / 30.48 cm