



## TENGEN CJX2-25 24v Contactor all models PWR and PWRC (Except PWR1 PWRC1)

### Key features

- Voltage Rating: Operates at 24V, making it suitable for low-voltage applications.
- Wide Compatibility: Designed to work with all PWR and PWRC models, except PWR1 and PWRC1, ensuring versatility in application.
- Easy Installation: Features a user-friendly design for quick installation and integration into existing systems.
- 3 Year Warranty, Customer Support and Service in the USA

### TENGEN CJX2-25 24v Contactor Description

The TENGEN CJX2-25 24V Contactor is designed for use in various PWR and PWRC series applications, excluding the PWR1 and PWRC1 models. This contactor provides reliable performance in controlling electrical circuits, ensuring safety and efficiency in your operational processes.

## Technical Specifications

|          |        |
|----------|--------|
| Warranty | 3 Year |
|----------|--------|

## Unit Weight & Dimensions

|                   |              |
|-------------------|--------------|
| Total Unit Weight | 1 lbs / 1 Kg |
|-------------------|--------------|

## Packaging Weight & Dimensions

|                      |              |
|----------------------|--------------|
| Package 1 Net Weight | 1 lbs / 0 Kg |
|----------------------|--------------|

|                 |                |
|-----------------|----------------|
| Package 1 Width | 5 in / 12.7 cm |
|-----------------|----------------|

|                        |                |
|------------------------|----------------|
| Package 1 Gross Weight | 1.2 lbs / 1 Kg |
|------------------------|----------------|

|                  |                |
|------------------|----------------|
| Package 1 Height | 5 in / 12.7 cm |
|------------------|----------------|

|                  |                |
|------------------|----------------|
| Package 1 Length | 5 in / 12.7 cm |
|------------------|----------------|