



1 Ton 2200 lbs Electric Chain Hoist 16ft. Japan FEC G80 Chain M3/H2 110~120V 13A 1800W Wireless

Key features

- High-efficiency Motor 1800W 13A @ 110V. Speed 13.2 ft per min
- Duty Class: H2/M3/1Bm/Class B. Protection IP54
- Wired and Wireless Control. Heavy duty Japan FEC Chain
- US and EU Standards ASME HST-1, ASME B30.16, IEC60204-32
- 3 Year Warranty, Customer Support and Service in the USA

Electric Chain Hoist Description

This **1 ton Electric Chain Hoist** uses a powerful motor to raise and lower loads up to 12 feet in the air. The single phase power supply makes it ideal for home or industrial applications. The hoist is easy to use which helps you complete large projects with ease.

Prowinch Electric Chain Hoist

All of our **Electric Chain Hoists** are created with the goal of offering the best price-performance ratio. Key components such as lifespan factors are constantly tested and improved in order to offer the best product for the price.

Key Components

All internal components have been upgraded to meet the highest quality standards. Key electronic components are produced by American or German brands, and we use American-made lubricants to ensure the lifespan of gears and reducers. Final assembly and all tests are performed in the US before shipping to ensure that every unit meets the corresponding standard.

Duty Classification

Duty classification is a key factor when choosing the right unit. These H2 hoists are suitable for general machine shop fabricating, assembly, storage, and warehousing. For uniformly distributed work periods, the hoists have 12.5% max. operational time per hour and can handle up to 75 starts per hour. When being used for infrequent work periods, the hoist can be operated for 15 minutes from a cold start with up to 100 starts per hour. Operational time ratings are calculated at a 65% load factor, as per ASME HST-1-2012.

Control System

This **Electric Chain Hoist** comes standard with an industrial wireless remote control and a pendant control. The length of the pendant control is 4 feet less than the lifting height, which allows it to be easily operated from ground-level.

Braking System

The **electromagnetic brake system** is tested at 125% of the hoist capacity and is designed to automatically engage immediately upon any loss of power.

Technical Specifications

Rated Load Capacity	2200 lb / 1000 kg	IEC Motor Protection	IP54
Standard Lifting Height	16 ft / 5 m	Control	Wireless JUUKO HS-K200NC2Q
Speed /min	13.2 ft / 4m	Control Voltage	110 V
Number of Speeds	1 Speed	Emergency Stop	Yes
Voltage	1 Phase 110~120V 60Hz	Contactors	Yes
Total Power Watts	1800W	Load Chain Type	FEC G80 Japan
FCC ID	RN489896162-B0129	Load Chain Size	7.1x20.2 mm
Buttons	Up, Down Emergency Stop	Chain Falls	1
Receiver Power Supply	110V	Chain Length	12 ft
Control Distance	300 ft	Humidity	<85%
Duty Class	H2/M3/1Bm/Class B	Temperature	-4 ~ 104° F / -20 ~ 40° C
Motor/Engine Power	1.8 kW	Noise Level	70 dB
Motor AMP	13	Standards Compliance	ASME HST-1 , ASME B30.16 , EN14492-2 , EN60204-32
Motor Brake	Yes	Warranty	3 Year
Insulation Grade	F		

Unit Weight & Dimensions

Total Unit Weight	71 lbs / 33 Kg
--------------------------	----------------

Packaging Weight & Dimensions

Package 1 Net Weight	71 lbs / 32 Kg
-----------------------------	----------------

Package 1 Width	13 in / 33.02 cm
------------------------	------------------

Package 1 Gross Weight	81 lbs / 37 Kg
-------------------------------	----------------

Package 1 Height	21 in / 53.34 cm
-------------------------	------------------

Package 1 Length	20 in / 50.8 cm
-------------------------	-----------------