

3000 kg Push Trolley Ex spark resistant series 3 t capacity



Key features

- Adheres to the Council Directive and Standards in the EU for explosion proof manual chain hoists. 94/9/EC : ATEX EN1127-1 :2008, EN13463-1 : 2009, EN13463-5 : 2003
- Atex Protection Grade II 2 GD c II B T105 °C
- 3 Year Warranty, Customer Support and Service in the USA

3000 kg Push Trolley Ex spark resistant series 2 ton capacity

Technical Specifications

Rated Load Capacity	3.15 ton / 6944 lbs	Minimum Turn Radius	1.7m [5.58 ft]
Load Test	150% [Rated Load / Capacidad Nominal]	Standards Compliance	ASME B30.17 / ATEX Directive
Explosion Proof Protection	Ex II 2 GD c II B T105 °C	Made in	Japan
Control	Manual Push	Warranty	3 Year
I-Beam Width Range	89 - 157.5 mm [3.5 - 6.2 in]		



Unit Weight & Dimensions

H Minimum Headroom	521 mm [20.5 in] Combined Hoist Trolley
X Wheels Diameter	114.3 mm [4.5 in]
Total Unit Weight	60 lbs / 28 Kg

Packaging Weight & Dimensions

Package 1 Net Weight	60 lbs / 27 Kg
-----------------------------	----------------