



13000 lb Heavy Duty Winch 480V 3 Phase Bonfiglioli (Italy) UL Certified Motor UL508A Control Variable Speed Made in USA

Key features

- Capacity: Supports up to 13,000 lbs, suitable for heavy-duty pulling and lifting applications.
- Power Supply: Operates on 480V 3-phase power, providing high power for demanding tasks.
- Motor: Features a Bonfiglioli (Italy) UL Certified Motor, known for its durability and reliability.
- 3 Year Warranty, Customer Support and Service in the USA

Winch Description

This heavy-duty winch features a 13,000 lb pulling capacity and is powered by a 480V 3-phase Bonfiglioli motor, renowned for its quality and reliability. UL certified and equipped with UL508A control for enhanced safety and compliance, it offers variable speed operation for precise control. Proudly made in the USA, this winch is designed for robust performance in demanding industrial and construction applications.

Technical Specifications

1st Layer Rated Capacity	13108 Lb / 5958 Kg @ 60HZ	Control	Pendant Control - 2 Button Emergency Stop and Speed Potentiometer
Rated Load Capacity	13000 lb	Control Voltage	24v DC
Last Layer Rated Capacity	6712 Lb / 3051 Kg	Electric Control Box	UL508A Certified Control Box - Made in USA
Number of Layers	9	Transmission / Reducer Type	Planetary Gear Reducer
Speed (f/m) / min	1st Layer 26 ft/min 9th Layer 50 ft/min @ 60HZ	Gear Ratio	186.25:1
Number of Speeds	Variable Speed	Drum Brake	Optional
Voltage	3 Phase 380~480V 50/60Hz	Free Spooling Clutch Type	No
Total Power Watts	11 kW	Recommended Wire Rope	Up to 1593 ft W63620A1, 6x36 IWRC ø 5/8 MS 41200 lb EIPS
Motor Type (68)	TEFC with DC Brake and Forced Vent	Humidity	<85%
Motor AMP	15.6 A	Standards Compliance	ASME B30.7 / UL508A / UL Type 4 / USA (UR) / Canada (CSA)
IEC Motor Protection	IP55	Made in	USA
IEC Electric Control Box Protection	IP66	Warranty	3 Year

Unit Weight & Dimensions

Drum BD Barrel Diameter (58)	ø260 mm
Drum DL Length (56)	707 mm
Drum FD Flange Diameter (57)	ø550 mm