



**15500 Lb Electric Winch
208~240/440~480V 3 Ph Wire Rope
ø22.4 mm x 500 ft, 1 Speed
Control, full Chasis, Motor and
Reducer Brake. Drum ø350mm**

Key features

- 3 Year Warranty, Customer Support and Service in the USA

Winch Description<

This robust 15500 lb electric winch operates on a 208~240V or 440~480V power supply and comes fully equipped with wire rope, a 1-speed control, and a comprehensive chassis. It features a high-performance motor with brake and a reducer second brake for enhanced safety and control. Designed for heavy-duty tasks, this winch provides reliable lifting and pulling capabilities, making it ideal for demanding industrial and construction applications.

Technical Specifications

1st Layer Rated Capacity	15580 lb / 7082 kg	Control	E-Stop/Up/Down - Optional Variable Speed
Last Layer Rated Capacity	4th Layer 11320 lb / 5146 Kg	Control Voltage	24V
Number of Layers	4	Electric Control Box	Included
Speed (f/m) / min	33~46 feet per minute	Gear Ratio	186.25:1
Number of Speeds	1 Speed - Optional Variable Speed	Drum Brake	Optional
Capacity Range	7	Wire Rope	Included
Voltage	3 Phase 208~240/440~480V 50/60Hz	Recommended Wire Rope	ø22.4 mm x 500 ft
Total Power Watts	15000	Humidity	<85%
Motor/Engine Type	Electric AC	Standards Compliance	ASME/ANSI B30.7, B30.10 / AWS D14.3 / RR-W-410E / ISO 2232
IEC Motor Protection	IP54	Warranty	3 Year
IEC Electric Control Box Protection	IP65	Standard Lifting Height	Up to 500 ft / 150 m

Unit Weight & Dimensions

A Total Height	860 mm	Package 1 Net Weight	2706 lbs / 1228 Kg
BD Barrel Diameter	ø350 mm		
D Depth	745 mm		
FD Flange Diameter	ø 560 mm		
W Width	1900 mm		
DL Drum Length	650 mm		
Total Unit Weight	2706 lbs / 1228 Kg		

Packaging Weight & Dimensions