



**2500 Lb Electric Winch
208~240/440~480V 3 Ph Wire Rope
ø10 mm x 200 ft , 1 Speed Control,
full Chasis, Motor and Reducer
Brake. Drum ø170mm**

Key features

- 3 Year Warranty, Customer Support and Service in the USA

Winch Description<

This robust 2400 lb electric winch operates on a 208~240V or 440~480V power supply and comes fully equipped with wire rope, a 1-speed control, and a comprehensive chassis. It features a high-performance motor with brake and a reducer second brake for enhanced safety and control. Designed for heavy-duty tasks, this winch provides reliable lifting and pulling capabilities, making it ideal for demanding industrial and construction applications.

Technical Specifications

1st Layer Rated Capacity	2570 lb / 1168 kg @ 60 Hz	Control	E-Stop/Up/Down - Optional Variable Speed
Last Layer Rated Capacity	5th Layer 1579 lb / 800 Kg	Control Voltage	24V
Number of Layers	5	Electric Control Box	Included
Speed (f/m) / min	51~75 feet per minute	Gear Ratio	59.7:1
Number of Speeds	1 Speed - Optional Variable Speed	Drum Brake	Optional
Capacity Range	2	Wire Rope	Included
Voltage	3 Phase 208~240/440~480V 50/60Hz	Recommended Wire Rope	ø10 mm x 200 ft
Total Power Watts	3730	Humidity	<85%
Motor/Engine Type	Electric AC	Standards Compliance	ASME/ANSI B30.7, B30.10 / AWS D14.3 / RR-W-410E / ISO 2232
IEC Motor Protection	IP54	Warranty	3 Year
IEC Electric Control Box Protection	IP65	Standard Lifting Height	Up to 200 ft / 60 m

Unit Weight & Dimensions

A Total Height	540 mm	Package 1 Net Weight	514 lbs / 233 Kg
BD Barrel Diameter	ø170 mm		
D Depth	410 mm		
FD Flange Diameter	ø320 mm		
W Width	950 mm		
DL Drum Length	220 mm		
Total Unit Weight	514 lbs / 234 Kg		

Packaging Weight & Dimensions