



# 3 ton 6600 lb 208~240/440~480V 2 Speed Electric Chain Hoist 30 ft. FEC G80 Japan Chain H4 Duty Wireless

### **Key features**

- Load Capacity: 3 tons (6600 lbs), suitable for heavy-duty lifting tasks.
- Voltage Range: 208~240/440~480V , compatible with various electrical systems.
- Speed Settings: 2 speeds, providing flexibility for different lifting requirements.
- 3 Year Warranty, Customer Support and Service in the USA

#### **Electric Chain Hoist Description**

The 3-ton (6600 lb) electric chain hoist offers versatile lifting capabilities with dual voltage options ( 208~240/440~480V). It features a 30 ft FEC G80 Japan chain, known for its high strength and durability. This hoist comes with a 2-speed motor, allowing precise control over lifting speeds to accommodate various operational needs. With an H4 duty rating, it is engineered for heavy-duty, continuous use in demanding environments. The wireless control system enhances operational efficiency and safety, enabling remote management of lifting tasks. Ideal for industrial applications requiring robust performance and flexibility.







## **Technical Specifications**

| But discitor of          | 6600 Hz - / 2000 Lz                                 | 6. del               | Window F21 Annal Bondon Control                   |
|--------------------------|---|----------------------|---|
| Rated Load Capacity      | 6600 lbs / 3000 kg                                  | Control              | Wireless F21-4 and Pendant Control                |
| Standard Lifting Height  | 30 ft / 9 m   | Control Voltage      | 24V   |
| Speed (f/m) / min        | 2.0 / 6.0 m/min                                     | Emergency Stop       | Yes   |
| Number of Speeds         | 2 Speed   | Load Chain Type      | G80 JAPAN   |
| Voltage                  | 3 Phase 208~240/440~480V 50/60Hz                    | Load Chain Size      | 11.2x34mm   |
| Available Voltages       | 208~240/440~480V for USA and 380/440~480V for CHILE | Chain Falls          | 1   |
| <b>Total Power Watts</b> | 3000  | Chain Length         | 30 ft / 9 m                                       |
| FCC ID                   | 2AZMK-Q1212   | Humidity             | <85%  |
| Duty Class               | H4/M5/2m/Class D                                    | Temperature          | -4 ~ 104° F / -20 ~ 40° C                         |
| Motor Power (6)          | 3 KW  | Noise Level          | 81 dB   |
| Motor Brake              | Yes   | Standards Compliance | UL 1340 - ASME HST-1 , ASME B30.16,<br>EN60204-32 |
| Insulation Grade         | F   | Warranty             | 3 Year  |
| IEC Motor Protection     | IP55  |                      |   |







## **Unit Weight & Dimensions**

## **Packaging Weight & Dimensions**

| H Minimum Headroom | 23 in / 57.5 cm   | Package 1 Net Weight | 273 lbs / 124 Kg |
|--------------------|-------------------|----------------------|------------------|
| W Width            | 27.5 in / 69.4 cm |                      |                  |
| D Depth            | 14 in / 35 cm     |                      |                  |
| J Hook Opening     | 1.53 in / 3.9 cm  |                      |                  |
| Total Unit Weight  | 273 lbs / 124 Kg  |                      |                  |