

5 ton 11000 lb 208~240/440~480V 1 Speed Electric Chain Hoist 30 ft. FEC G80 Japan Chain H4 Duty Wireless

Key features

- Load Capacity: 5 tons (11,000 lbs), ideal for heavy-duty lifting tasks.
- Voltage Range: 208~240/440~480V, adaptable to various electrical systems.
- Speed Setting: 1 speed, suitable for straightforward lifting operations.
- 3 Year Warranty, Customer Support and Service in the USA

Electric Chain Hoist Description

This robust 5-ton (11,000 lb) electric chain hoist is designed for heavy-duty lifting tasks. It operates on dual voltage options (208~240/440~480V) and is equipped with a 1-speed motor for straightforward, reliable performance. The 30 ft FEC G80 Japan chain ensures exceptional strength and durability, meeting the demands of rigorous industrial environments. With an H4 duty rating, this hoist is built for continuous use and high operational efficiency. The included wireless control provides enhanced convenience and safety by allowing remote operation. Ideal for a wide range of heavy lifting applications where reliability and ease of use are essential.

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com






PWJF50H4-1SW

Technical Specifications

| UL File | MSXT.E528915 - Hoists | Control | Wireless F21-4 and Pendant Control |
|-------------------------|---|----------------------|---|
| Rated Load Capacity | 11000 lbs / 5000 kg | Control Voltage | 24V |
| Standard Lifting Height | 30 ft / 9 m | Emergency Stop | Yes |
| Number of Speeds | 1 Speed | Load Chain Type | G80 JAPAN |
| Voltage | 3 Phase 208~240/440~480V 50/60Hz | Load Chain Size | 11.2x34mm |
| Available Voltages | 208~240/440~480V for USA and 380/440~480V for CHILE | Chain Falls | 2 |
| FCC ID | 2AZMK-Q1212 | Chain Length | 60 ft / 18 m |
| Duty Class | H4/M5/2m/Class D | Humidity | <85% |
| Motor Power | 3 KW | Temperature | -4 ~ 104° F / -20 ~ 40° C |
| Motor Brake | Yes | Noise Level | 81 dB |
| Insulation Grade | F | Standards Compliance | UL 1340 - ASME HST-1 , ASME B30.16, EN60204-32 |
| IEC Motor Protection | IP55 | Warranty | 3 Year |

Unit Weight & Dimensions

| W Width | 27.5 in / 69.4 cm | Package 1 Net Weight | 321 lbs / 146 Kg |
|-------------------|-------------------|----------------------|------------------|
| J Hook Opening | 2.72 in / 6.9 cm | | |
| Total Unit Weight | 321 lbs / 146 Kg | | |



Packaging Weight & Dimensions

prowinch.com

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com

