



# 3000 lbs Powered Electric Winch Waterproof 12V DC

## **Key features**

- Sturdy 3,000lb rated line pull powered by 1 horsepower 12V DC motor.
- Low-amp, permanent magnet motor; Gear Ratio- 166:1
- Pull and turn free spooling clutch; Gearing 3 Stage Planetary.
- Reliable Drum Brake Designed to Automatically Engage upon any Loss of Power.
- 1 Year Warranty, Customer Support and Service in the USA

### **Winch Description**

This **3,000 lbs Electric ATV/UTV Winch 12V** will get you out of any sticky situation. Whether you are in the dirt, mud, or snow this dependable winch is the vital partner every rider needs. With an impressive 3,000lb load capacity and 1HP motor, this electric winch will give you the results you need. Use this winch with confidence as it includes a 1 Year Warranty

#### **Prowinch Electric DC Winches**

All of our electric DC winches are created with the goal of offering the best price-performance ratio. Key components such as lifespan factors are constantly tested and improved in order to offer the best product for the price.

#### **Key Components**

All internal components have been upgraded to meet the highest quality standards. Key electronic components are produced by American or German brands, and we use American-made lubricants to ensure the lifespan of gears and reducers. Final assembly and all tests are performed locally at Prowinch facility before shipping to ensure that every unit meets the corresponding standard.

#### **Control System**

This winch includes a 12V wired remote control. The winch contains the best electric components available on the market, and everything is made, assembled, and tested locally in the US, Chile, or Colombia.

#### **Braking System**


Prowinch electric DC winches include a sliding ring gear clutch and an in drum automatic brake. Automatic brake system designed to automatically engage immediately upon any loss of power.





# **Technical Specifications**

1st Layer Rated Capacity	3000 lbs	Motor AMP	230 AMP
Speed /min	6~23 ft / 1.9~7.1 m	IEC Motor Protection	IP67
Number of Speeds	1 Speed	Control	Wired Remote Control
Wire rope capacity per layer first/last	3,000 / 1,779	Transmission / Reducer Type	3-Stage Planetary
Voltage	Battery Power 12 VDC	Gear Ratio	166:1
FCC ID	2ASYP-DW12K	Drum Brake	In-Drum Automatic Brake
Duty Class	Recovery / Rescate	Free Spooling Clutch Type	Cam Activated
Motor/Engine Type	DC Permanent Magnet Motor	Wire Rope	Steel ø3/16 in x 50 ft   ø4.8mm x 15 m
Motor/Engine Power	1 HP	Warranty	1 Year





#### INCLUDED/ INCLUIDO







**Packaging Weight & Dimensions** 



Dimensions in mm / Dimensiones en mm

# **Unit Weight & Dimensions**

A Total Height	114 mm	Package 1 Net Weight	17 lbs / 8 Kg
DL Drum Length	74 mm	Package 1 Width	11 in / 27.94 cm
W Width	335 mm	Package 1 Gross Weight	26 lbs / 12 Kg
J Hook Opening	15.5 mm	Package 1 Height	7 in / 17.78 cm
<b>BD Barrel Diameter</b>	50 mm	Package 1 Length	15 in / 38.1 cm
Total Unit Weight	17 lbs / 8 Kg		