



# 3000 lbs Powered Electric Winch Waterproof 12V DC

### **Key features**

- Maximum Pulling Capacity: Rated for 3,000 lbs, ideal for light-duty applications such as ATVs, UTVs, trailers, and smaller vehicles.
- 12V DC Power: Runs on a 12-volt system, compatible with most standard automotive and recreational vehicle batteries.
- Waterproof Construction: Fully waterproof design to withstand harsh weather conditions like rain, mud, and snow.
- 1 Year Warranty, Customer Support and Service in the USA

#### **Winch Description**

This 3,000 lbs Electric ATV/UTV Winch 12V will get you out of any sticky situation. Whether you are in the dirt, mud, or snow this dependable winch is the vital partner every rider needs. With an impressive 3,000lb load capacity and 1HP motor, this electric winch will give you the results you need. Use this winch with confidence as it includes a 1 Year Warranty

#### **Prowinch Electric DC Winches**

All of our electric DC winches are created with the goal of offering the best price-performance ratio. Key components such as lifespan factors are constantly tested and improved in order to offer the best product for the price.

#### **Key Components**

All internal components have been upgraded to meet the highest quality standards. Key electronic components are produced by American or German brands, and we use American-made lubricants to ensure the lifespan of gears and reducers. Final assembly and all tests are performed locally at Prowinch facility before shipping to ensure that every unit meets the corresponding standard.

#### **Control System**

This winch includes a 12V wired remote control. The winch contains the best electric components available on the market, and everything is made, assembled, and tested locally in the US, Chile, or Colombia.

#### **Braking System**

Prowinch electric DC winches include a sliding ring gear clutch and an in drum automatic brake. Automatic brake system designed to automatically engage immediately upon any loss of power.






## **Technical Specifications**

Number of Layers       4       Transmission / Reducer Type       3-Stage Planetary         Speed (f/m) / min       6~23 ft / 1.9~7.1 m       Gear Ratio       166:1         Number of Speeds       1 Speed       Drum Brake       Automatic         Voltage       Battery Power 12 VDC       Free Spooling Clutch Type       Cam Activated         FCC ID       2ASYP-DW12K       Wire Rope       Steel ø3/16 in x 50 ft   ø4.8mm x 15 m         Motor Type (68)       DC Permanent Magnet Motor       Fairlead       Included         Motor AMP       230 AMP       Accessories       Control and Installation Hardware         IEC Motor Protection       IP67       Warranty       1 Year	1st Layer Rated Capacity	3000 lbs	Control Voltage	12 V
Number of Speeds1 SpeedDrum BrakeAutomaticVoltageBattery Power 12 VDCFree Spooling Clutch TypeCam ActivatedFCC ID2ASYP-DW12KWire RopeSteel ø3/16 in x 50 ft   ø4.8mm x 15 mMotor Type (68)DC Permanent Magnet MotorFairleadIncludedMotor AMP230 AMPAccessoriesControl and Installation Hardware	Number of Layers	4	Transmission / Reducer Type	3-Stage Planetary
VoltageBattery Power 12 VDCFree Spooling Clutch TypeCam ActivatedFCC ID2ASYP-DW12KWire RopeSteel ø3/16 in x 50 ft   ø4.8mm x 15 mMotor Type (68)DC Permanent Magnet MotorFairleadIncludedMotor AMP230 AMPAccessoriesControl and Installation Hardware	Speed (f/m) / min	6~23 ft / 1.9~7.1 m	Gear Ratio	166:1
FCC ID  2ASYP-DW12K  Wire Rope  Steel ø3/16 in x 50 ft   ø4.8mm x 15 m  Motor Type (68)  DC Permanent Magnet Motor  Fairlead  Included  Motor AMP  230 AMP  Accessories  Control and Installation Hardware	Number of Speeds	1 Speed	Drum Brake	Automatic
Motor Type (68)  DC Permanent Magnet Motor Fairlead Included  Motor AMP  230 AMP Accessories Control and Installation Hardware	Voltage	Battery Power 12 VDC	Free Spooling Clutch Type	Cam Activated
Motor AMP 230 AMP Accessories Control and Installation Hardware	FCC ID	2ASYP-DW12K	Wire Rope	Steel ø3/16 in x 50 ft   ø4.8mm x 15 m
	Motor Type (68)	DC Permanent Magnet Motor	Fairlead	Included
IFC Motor Protection IP67 Warranty 1 Year	Motor AMP	230 AMP	Accessories	Control and Installation Hardware
Transfer in the second of the	IEC Motor Protection	IP67	Warranty	1 Year

**Control** Wired Remote Control





#### INCLUDED/ INCLUIDO



**Packaging Weight & Dimensions** 



Dimensions in mm / Dimensiones en mm

## **Unit Weight & Dimensions**

A Total Height	114 mm	Package 1 Net Weight	17 lbs / 8 Kg
Drum DL Length (56)	74 mm	Package 1 Width	11 in / 27.94 cm
W Width	335 mm	Package 1 Gross Weight	26 lbs / 12 Kg
J Hook Opening	15.5 mm	Package 1 Height	7 in / 17.78 cm
Drum BD Barrel Diameter (58)	50 mm	Package 1 Length	15 in / 38.1 cm
Total Unit Weight	17 lbs / 8 Kg		