



2 ton 4400 lb Electric Wire Rope Hoist 24 mts. 4 ways 2 Speed H3 Duty Wireless

Key features


- Load Capacity: 2 tons (4,400 lbs), ideal for medium-heavy lifting tasks.
- Lifting Height: 24 meters (approximately 79 feet), suitable for high lifting needs.
- Speed: 2 Speed settings for precise and controlled lifting and lowering.
- 3 Year Warranty, Customer Support and Service in the USA

Electric Wire Rope Hoist Description

2 Ton Wireless Electric Wire Rope Hoists are used for raising and lowering material. Power Cord is standard at 3 ft. for Hook and Push Trolley Mounts. Power Cord is standard at 3 ft. for Motorized Trolley Mounts. Hoists usually ship within 1-3 business days after ordering. Please call us at 1 (800) 971-8061 for any special requests. The Highest Quality, most Technologically Advanced Hoist in the Industry. Our hoist ranges from basic Light Duty H1 to Heavy Duty Motor - 60 minute, H4 classification, Class B insulation with cooling fins and standard thermal motor protection. Compact lightweight body offers one of the lowest headroom hoists in the industry. Extremely durable and reliable Pull Rotor Motor Brake. Contains NO brake coil to fail like conventional disc brakes. Durable Push-Button Pendant for easy, one-handed operation. (Now with an included professional Industrial wireless remote control kit). Double speed functionality allows for a precise maneuverability and precision. Includes strain relief wire molded to pendant cord for added support and reliability. Easy Maintenance Control Panel is hinged to swing out to provide fast, easy, and trouble-free access. Completely Sealed Body suitable for both indoor and outdoor applications, including harsh environments. Gaskets throughout the hoist provide an IP55 rating. Oil Bath and precision machined helical and spur gears provide for quiet, smooth, and cool operations.

Technical Specifications

Rated Load Capacity	4400 lb / 2000 kg	Control	Pendant Control and Optional Wireless F21
Standard Lifting Height	80 ft / 24 m	Control Voltage	24 V
Speed (f/m) / min	3-26 ft / 0.8-8 m	Contactors	Schneider or EATON
Number of Speeds	2 Speed	Wire Rope	ø9/16 in x 79 ft ø13 mm x 48 m
Voltage	3 Phase 380V 50Hz	Humidity	<85%
Available Voltages	460V-US / 380V-CHILE	Temperature	-4°~104° F / -20°~40° C
Duty Class	H3/M4/1Am/Class C	Trolley Power	0.4 kW 3 Ph
Motor Type (68)	Squirrel Cage Induction Motor	Noise Level	82 dB
Motor Power (6)	0.4-3 kW	Trolley Speed /min	66 ft / 20 m
Motor RPM	1728@60Hz 1440@50HZ	I-Beam Width Range	100~134 mm [3.9~5.3 in]
Insulation Grade	F	Minimum Turn Radius	13 ft / 4 m
IEC Motor Protection	IP55	Standards Compliance	ASME HST-4 , ASME B30.16 , B30.17 , EN14492-2 , EN60204-32
Dynamic Brake	Optional with VFD Driver	Warranty	3 Year



Unit Weight & Dimensions

A Total Height	29.1 in / 740 mm
W Width	63 in / 1600 mm
D Depth	35.43 in / 900 mm
Total Unit Weight	662 lbs / 301 Kg

Packaging Weight & Dimensions

Package 1 Net Weight	662 lbs / 300 Kg
Package 1 Width	19 in / 48.26 cm
Package 1 Gross Weight	692 lbs / 314 Kg
Package 1 Height	26 in / 66.04 cm
Package 1 Length	61 in / 154.94 cm