

5 ton Wire Rope Hoist with Trolley 35 mts. 2 Speed M4 / 1Am



Key features

- Load Capacity: 5 tons (11,000 lbs), suitable for medium to heavy lifting tasks.
- Lifting Height: 35 meters (approximately 115 feet), accommodating high-lift needs.
- Speed: 2 Speed settings, allowing for controlled and efficient load handling.
- 3 Year Warranty, Customer Support and Service in the USA

Electric Wire Rope Hoist Description

5 Ton Wireless Electric Wire Rope Hoists are used for raising and lowering material. Power Cord is standard at 3 ft. for Hook and Push Trolley Mounts. Power Cord is standard at 3 ft. for Motorized Trolley Mounts. Hoists usually ship within 1-3 business days after ordering. Please call us at 1 (800) 971-8061 for any special requests. The Highest Quality, most Technologically Advanced Hoist in the Industry. Our hoist ranges from basic Light Duty H1 to Heavy Duty Motor - 60 minute, H4 classification, Class F insulation with cooling fins and standard thermal motor protection. Compact lightweight body offers one of the lowest headroom hoists in the industry. Extremely durable and reliable Pull Rotor Motor Brake. Contains NO brake coil to fail like conventional disc brakes. Durable Push-Button Pendant for easy, one-handed operation. (Now with an included professional Industrial wireless remote control kit). Includes strain relief wire molded to pendant cord for added support and reliability. Easy Maintenance Control Panel is hinged to swing out to provide fast, easy, and trouble-free access. Completely Sealed Body suitable for both indoor and outdoor applications, including harsh environments. Gaskets throughout the hoist provide an IP55 rating. Oil Bath and precision machined helical and spur gears provide for quiet, smooth, and cool operations.

Technical Specifications

Rated Load Capacity	11000 lb / 5000 kg	Control	Pendant Control and Optional Wireless F21
Number of Speeds	2 Speed	Control Voltage	24 V
Voltage	3 Phase 208~240/440~480V 50/60Hz	Contactors	Schneider or EATON
Available Voltages	460V-US / 380V-CHILE	Humidity	<85%
Duty Class	H3/M4/1Am/Class C	Temperature	-4°~104° F / -20°~40° C
Motor Type (68)	Squirrel Cage Induction Motor	Noise Level	82 dB
Motor RPM	1728@60Hz 1440@50HZ	I-Beam Width Range	116~154 mm [4.6~6.1 in]
Insulation Grade	F	Standards Compliance	ASME HST-4 , ASME B30.16 , B30.17 , EN14492-2 , EN60204-32
IEC Motor Protection	IP55	Warranty	3 Year
Dynamic Brake	Optional with VFD Driver		

Unit Weight & Dimensions

Total Unit Weight	1350 lbs / 613 Kg
--------------------------	-------------------

Packaging Weight & Dimensions

Package 1 Net Weight	1350 lbs / 613 Kg
Package 1 Width	24 in / 60.96 cm
Package 1 Gross Weight	1380 lbs / 626 Kg
Package 1 Height	33 in / 83.82 cm
Package 1 Length	91 in / 231.14 cm