



10 Tons Double Girder Top Running Overhead Crane

Key features

- Load Capacity: Capable of lifting up to 10 tons, perfect for heavy industrial applications.
- Top Running Configuration: Optimizes headroom and allows for smooth, efficient movement along the runway.
- Versatile Applications: Suitable for warehouses, manufacturing facilities, and construction sites where heavy lifting is required.
- 3 Year Warranty, Customer Support and Service in the USA

The 10 Tons Double Girder Top Running Overhead Crane Description

The 10 Tons Double Girder Top Running Overhead Crane is designed for heavy-duty lifting in industrial environments. This robust crane features a double girder configuration for enhanced stability and load distribution, making it ideal for moving heavy materials and equipment across large spans.

Technical Specifications

| | |
|----------|--------|
| Warranty | 3 Year |
|----------|--------|




| Model/Modelo | PWMS10T |
|---|---------------------------|
| Capacity Capacidad | 22046 lb / 10000 kg |
| Speed Velocidad | 2.6 - 16 ft / 0.8 - 5m |
| Traveling Speed (per min) Velocidad Desplazamiento (por min) | 16.4 - 65.6 ft / 5 - 20 m |
| Lifting Height Altura de Izaje | 39 ft / 12 m |
| Lifting Motor Motor de Izaje | 1.5 - 9.5 kW |
| Traveling Motor Motor de Desplazamiento | 0.37 kW x 2 |
| Duty Class Clase de Servicio | M5 |

6 way remote control and two speeds / control remoto 6 vías y doble velocidad



| Model/Modelo | PWLH10T |
|--|---------------------|
| Capacity Capacidad | 22046 lb / 10000 kg |
| Length Largo | 59 ft / 18 m |
| Traveling Length Distancia Desplazamiento | 164 ft / 45 m |
| Duty Class Clase de Servicio | M4 |



| Model/Modelo | PWSP10T |
|--|-------------------------|
| Capacity Capacidad | 22046 lb / 10000 kg |
| Length Largo | 11 ft / 3.5 m |
| Speed (per min) Velocidad (por min) | 13 - 65.6 ft 4 - 20 m |
| Motor Power Potencia Motor | 0.75 kW |
| Gear Diameter Diámetro Engranaje | 9.64 in / 245 mm |
| Duty Class Clase de Servicio | M4 |

| | |
|---|--|
| Standard | ASME B30.2 / ANSI Z535.4 / ANSI / ASCE 7-88 / ANSI Z244.1 / ANSI AA1264.1 / ANSI / SAE Z26.1 / ANSI A14.3 CMAA No. 70-2000 / AISE No.6 |
| Norma | |
| Warranty: 3 Year / Certification valid for 1 year / 10 year parts and service availability | |
| Garantía: 3 Años / Certificación válida por 1 año / 10 Años disponibilidad de piezas y servicio | |

