



Bridge Crane with Hoist 20 Tons

Key features

- Load Capacity: Designed to lift up to 20 tons, making it suitable for the most rigorous industrial applications.
- Top Running Design: Maximizes headroom and ensures smooth movement along the runway, optimizing operational efficiency.
- Versatile Applications: Perfect for use in warehouses, manufacturing plants, and construction sites where heavy lifting is essential.
- 3 Year Warranty, Customer Support and Service in the USA

The 20 Tons Double Girder Top Running Overhead Crane Description

The 20 Tons Double Girder Top Running Overhead Crane is engineered for heavy-duty lifting in demanding industrial environments. With its double girder design, this crane offers exceptional strength, stability, and load handling capabilities, making it ideal for transporting substantial materials and equipment.







Technical Specifications

Warranty

3 Year







Model/Modelo	PWMS20T
Capacity	44092 lb / 20000 kg
Capacidad	
Speed (per min)	2 -13 ft / 0.6 - 4 m
Velocidad (por min)	2-13 11 / 0.6 - 4 111
Traveling Speed (per min)	16.4 - 65.6 ft / 5 - 20 m
Velocidad Desplazamiento (por min)	
Lifting Height	39 ft / 12 m
Altura de Izaje	39 11 / 12 111
Lifting Motor	2.6 - 16 kW
Motor de Izaje	2.6 - 16 KW
Traveling Motor	0.55 kW x 2
Motor Desplazamiento	0.35 KW X Z
Duty Class	M5
Clase de Servicio	



Model/Modelo	PWLH20T
Capacity	44092 lb / 20000 kg
Capacidad	
Length	59 ft / 18 m
Longitud	
Traveling Length	164 ft / 45 m
Distancia Desplazamiento	
Duty Class	M4
Class de Cassisia	



Model/Modelo	PWSP20T
Capacity	44092 lb / 20000 kg
Capacidad	44032 IB / 20000 Kg
Length	9.8 ft / 3 m
Longitud	
Speed (per min)	13 - 65.6 ft / 4 - 20 m
Velocidad (por min)	13 - 63.6 11 / 4 - 20 111
Motor Power	1.5 kW
Potencia Motor	
Gear Diameter	13.3 in / 340 mm
Diámetro Engranaje	13.3 111 / 340 111111
Duty Class	M4
Clase de Servicio	

Standard	ASME B30.2 / ANSI Z535.4 / ANSI / ASCE 7-88 /
Norma	ANSI Z244.1 / ANSI AA1264.1 / ANSI/ SAE Z26.1 / ANSI A14.3 CMAA No. 70-2000 / AISE No.6
Warranty: 3 Year / Certifica	tion valid for 1 year / 10 year parts and service availability
Garantía: 3 Años / Certificació	n valida por 1 año / 10 Años disponibilidad de piezas y servicio







