



3 Tons Single Girder Top Running Underhung Chain Hoist Crane

Key features

- Load Capacity: Lifts up to 3 tons, ideal for a variety of applications in manufacturing, assembly lines, and warehouses.
- Top Running Configuration: Ensures smooth operation along the runway, allowing for efficient movement and workflow.
- Durable Construction: Built with high-quality materials to withstand demanding environments and ensure long-lasting performance.
- 3 Year Warranty, Customer Support and Service in the USA

The 3 Tons Single Girder Top Running Underhung Hoist Crane Description

The 3 Tons Single Girder Top Running Underhung Hoist Crane is designed for efficient lifting and maneuverability in industrial settings. This crane is perfect for handling loads up to 3 tons while maximizing space and improving operational efficiency.




Technical Specifications

Warranty	3 Year
----------	--------




Standard	ASME B30.11/ ANSI Z535.4/ ANSI/ ASCET-88/ ANSI Z244.1/ ANSI A1264.1/ ANSI/ SAE Z26.1/ ANSI A14.3 CMAA No. 70-2000/ AISE No.6
Norma	

Dimensions in mm / Dimensiones en mm



VISTA EN ELEVACION CARGA A IZAR: 1 TONELADA ESCALA 1:100




DETALLE CARGA A IZAR: 1 TONELADA ESCALA 1:25

Model/Modelo	PWMS3T
Capacity Capacidad	6614 lb / 3000 kg
Lifting Speed (per min) Velocidad de Izaje (por min)	13.2 ft / 4.4 m
Traveling Speed (per min) Velocidad Desplazamiento (por min)	36 ft / 11 m
Lifting Motor Motor de Izaje	1-3 kW
Lifting Height Altura de Izaje	15 ft / 4.61 m
Traveling Motor Motor de Desplazamiento	0.75 kW
Duty Class Clase de Servicio	M4



Model/Modelo	PWLH3T
Capacity Capacidad	6614 lb / 3000 kg
Length Largo	20.3 ft / 6.2 m
Traveling Length Distancia Desplazamiento	46.2 ft / 14.1 m
Rail Gage Distance Ancho de la Viga	3.22 in / 82 mm
Duty Class Clase de Servicio	M4



Model/Modelo	PWSP3T
Capacity Capacidad	6614 lb / 3000 kg
Length Largo	6.5 ft / 2 m
Traveling Speed (per min) Velocidad Desplazamiento (por min)	65.6 ft / 20m
Motor Power Potencia Motor	0.4 kW
Gear Diameter Diámetro Engranaje	5.70 in / 145 mm
Duty Class Clase de Servicio	M4