

## 7.5 Ton 2 Speed Power Trolley 220/460V 60HZ with Limit Switches Pendant not Included


### Key features

- Quality is inside: Heavy Duty H3/M4. Aluminum housing, NSK Bearings, USA Chevron Meropa 320 Lub
- US Brand EATON Contactors, All ways Limit Switches, Emergency Stop
- US and EC Standards ASME HST-1 , ASME B30.16 , EN14492-2 , EN60204-32
- 3 Year Warranty, Customer Support and Service in the USA

7.5 Ton 2 Speed Power Trolley 230/460V 60HZ with Limit Switches Pendant not Included

## Technical Specifications

<b>Rated Load Capacity</b>	15400 lb / 7000 kg	<b>I-Beam Width Range</b>	100-178 mm
<b>Voltage</b>	3 Phase 208~240/440~480V 50/60Hz	<b>Minimum Turn Radius</b>	5.9 ft / 1.8 m
<b>Trolley Speed /min</b>	36 - 68 ft /11 - 21 m	<b>Warranty</b>	3 Year



Model / Modelo		PWQE1Ti	PWQE2Ti	PWQE3Ti	PWQE5Ti	PWQE7Ti	PWQE10Ti
Dimensions / Dimensiones	<b>W</b>	12.4 in / 315mm	12.7 / 325mm	13.3in / 340mm	15.7 in/ 400mm	26.5 in / 670 mm	19.6in / 500mm
	<b>U</b>	8.3 in / 212mm	8.6mm / 220mm	9.8 in / 250mm	11.4 in / 291mm	-	14.6in / 371mm
	<b>R</b>	5.5 in / 142mm	5.5 in / 142mm	5.5 in / 142mm	5.5 in / 142mm	9 in / 231 mm	5.5 in / 142mm
	<b>T</b>	9 in / 231mm	9 in / 231mm	9 in / 231mm	9 in / 231mm	5.6 in / 142 mm	9 in / 231mm

## Unit Weight & Dimensions

<b>T Trolley Motor Width</b>	5.6 in / 142 mm	<b>Package 1 Net Weight</b>	173.8 lbs / 79 Kg
<b>D Depth</b>	17 in / 430 mm	<b>Package 1 Gross Weight</b>	184.8 lbs / 84 Kg
<b>R Trolley Cover Width</b>	9 in / 231 mm		
<b>W Width</b>	26.5 in / 670 mm		
<b>Total Unit Weight</b>	173.8 lbs / 79 Kg		

## Packaging Weight & Dimensions