



# 1 ton Electric Chain Hoist 1 Speed 110V 1ø 60HZ 20ft G100 Nickel Wireless FCC Certificate Duty H2/M3

#### **Key features**

- Load Capacity: 1 ton (2,200 lbs), suitable for lifting medium to heavy loads.
- Voltage: 110V, Single Phase, 60Hz, compatible with standard electrical systems.
- Speed Setting: 1 Speed, ensuring consistent and straightforward operation.
- 3 Year Warranty, Customer Support and Service in the USA

#### **Electric Chain Hoist Description**

Boost your lifting efficiency with this 1-ton electric chain hoist, featuring a single-speed operation and a 20 ft. G100 chain. Operating on 110V single-phase 60HZ power, it includes a durable nickel finish and convenient wireless control. The FCC certification ensures compliance with safety standards, while the H2/M3 duty rating makes it ideal for medium-duty industrial tasks. Perfect for versatile lifting needs, this hoist delivers both performance and convenience.





## **Technical Specifications**

| Rated Load Capacity         | 1 ton   | Chain Falls                    | 2  |
|-----------------------------|---|--------------------------------|--|
| Standard Lifting Height     | 20 ft / 6 m   | Chain Length                   | 40                                       |
| Number of Speeds            | 1 Speed   | Humidity                       | 20%~90%                                  |
| Voltage                     | 1 Phase 110~120V 60Hz                                   | Temperature                    | -4 ~ 104° F / -20 ~ 40° C                |
| Total Power Watts           | 750   | Standards Compliance           | ASME HST-1 , ASME B30.16 ,<br>EN60204-36 |
| IEC Motor Protection        | IP55  | Warranty                       | 3 Year                                   |
| Control                     | Pendant Control IP66 and Industrial<br>Wireless Control | Hoist Motor Power in KW        | 0,75                                     |
| Control Voltage             | 24V   | Hoist Motor Insulation Grade   | F  |
| Emergency Stop              | Yes   | Hoist Contactor Coil Voltage   | 24 V                                     |
| Transmission / Reducer Type | Spur gearbox  | Hoist Contactors Amps          | 25A                                      |
| Load Chain Type             | G100 Nikel  | IEC Hoist IP Protection        | IP55                                     |
| Load Chain Size             | 7.1 mm  | IEC Pendant Control Protection | IP66                                     |

### **Unit Weight & Dimensions**

## **Packaging Weight & Dimensions**

| H Minimum Headroom                  | 810              | Package 1 Net Weight   | 294,8 lbs / 133 Kg |
|-------------------------------------|------------------|------------------------|--------------------|
| J Hook Opening                      | 60               | Package 1 Width        | 20 in / 50.8 cm    |
| A Total Height                      | 675              | Package 1 Gross Weight | 319 lbs / 145 Kg   |
| Total Weight (w/out cable or Chain) | 265.23           | Package 1 Height       | 31 in / 78.74 cm   |
| D Depth                             | 695              | Package 1 Length       | 30 in / 76.2 cm    |
| 1st Package Type                    | Wood Crate       |                        |                    |
| W Width                             | 420              |                        |                    |
| Total Unit Weight                   | 294 lbs / 134 Ka |                        |                    |