



1 ton Electric Chain Hoist 1 Speed 208~240V 3ø 60HZ 16ft G100 Nickel Duty H4/M5

Key features

- Load Capacity: 1 ton (2,200 lbs), designed for heavy-duty lifting applications.
- Voltage: 208~240V, 3-phase, 60Hz, suitable for industrial power setups.
- Speed Setting: 1 Speed, ensures smooth and steady operation.
- 3 Year Warranty, Customer Support and Service in the USA

Electric Chain Hoist Description

This 1-ton electric chain hoist delivers top-tier performance with a 208~240V 3-phase motor running at 60HZ, providing consistent lifting power. Equipped with a 16 ft. G100 nickel-plated chain, it's built for strength and durability. Rated for H4/M5 duty, this hoist is designed for heavy-duty industrial use, ideal for frequent and demanding lifting tasks. Reliable and efficient, it's perfect for tough environments that require superior lifting capabilities.

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com





Technical Specifications

| Rated Load Capacity | 1 ton | Chain Falls | 1 |
|-----------------------------|--|--------------------------------|--|
| Standard Lifting Height | 16 ft / 5 m | Chain Length | 16 |
| Speed (f/m) / min | 25,59 ft @60Hz 6,5 mt @50Hz | Humidity | 20%~90% |
| Number of Speeds | 1 Speed | Temperature | -4 ~ 104° F / -20 ~ 40° C |
| Voltage | 3 Phase 208~240V 50/60Hz | Standards Compliance | ASME HST-1 , ASME B30.16 , EN60204-33 |
| Total Power Watts | 1500 | Warranty | 3 Year |
| Duty Class | H4/M5/2m/Class D | Hoist Motor Power in KW | 1,5 |
| IEC Motor Protection | IP55 | Hoist Motor Insulation Grade | F |
| Control | Pendant Control IP66 and Optional Wireless | Hoist Contactor Coil Voltage | 24 V |
| Control Voltage | 24V | Hoist Contactors Amps | 18A |
| Emergency Stop | Yes | Hoist Contactor Brand | sokar |
| Transmission / Reducer Type | Spur gearbox | IEC Hoist IP Protection | IP55 |
| Load Chain Type | G100 Nikel | IEC Pendant Control Protection | IP66 |
| Load Chain Size | 7.1 mm | | |

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com





Unit Weight & Dimensions

Packaging Weight & Dimensions

| H Minimum Headroom | 516 | Package 1 Net Weight | 101,64 lbs / 46 Kg |
|--|-----------------|------------------------|--------------------|
| J Hook Opening | 42 | Package 1 Width | 16 in / 40.64 cm |
| A Total Height | 455 | Package 1 Gross Weight | 121 lbs / 55 Kg |
| Total Weight (w/out cable or Chain) | 89.81 | Package 1 Height | 26 in / 66.04 cm |
| D Depth | 590 | Package 1 Length | 26 in / 66.04 cm |
| 1st Package Type | Wood Crate | | |
| W Width | 330 | | |
| Total Unit Weight | 101 lbs / 46 Kg | | |

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com

