



5 Ton Electric Chain Hoist Power Trolley 30 ft. FEC G80 Japan Chain M5/H4 380V~480V Variable Speed

Key features

- Load Capacity: 5 tons (11,000 lbs), designed for heavy-duty industrial lifting.
- Speed: Single-speed hoist for consistent and controlled lifting.
- Power Trolley: Efficient powered trolley mechanism, providing smooth horizontal movement along beams.
- 3 Year Warranty, Customer Support and Service in the USA

Electric Chain Hoist Description

This **5 ton Electric Chain Hoist with Power Trolley** uses a powerful motor to raise and lower loads up to 30 feet in the air. The three-phase power supply and M5 duty cycle make it ideal for industrial applications. The hoist is easy to use, and the convenient trolley helps you complete even the largest projects with ease.

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com





PWRC5M5VS

Technical Specifications

Rated Load Capacity	11000 lb / 5000kg	Control	Pendant Control and Optional Wireless
Standard Lifting Height	30 ft / 9 m	Control Voltage	24V
Number of Speeds	Variable Speed	Emergency Stop	Yes
Voltage	3 Phase 380~480V 50/60Hz	Transmission / Reducer Type	Spur gearbox with Oil splash lubrication
USA and Canada Voltage	VFD 380~500V	Load Chain Type	FEC G80 Japan
Duty Class	H4/M5/2m/Class D	Trolley VFD	2.2KW VFD, Delta model: VFD5A5MS43ANSAA
Motor Brake	Yes DC Electromagnetic	Trolley Power	0.8 kW
Insulation Grade	F	Noise Level	81 dB
IEC Motor Protection	IP55	Trolley Number of Speeds	Variable
Variable Fequency Driver	3.7KW VFD, Delta model: VFD9A0MS43ANSAA	Standards Compliance	ASME HST-1 , ASME B30.16 , B30.17 , EN60204-32
Dynamic Brake	Yes	Warranty	3 Year

Packaging Weight & Dimensions

Package 1 Gross Weight	533 lbs / 242 Kg
Package 1 Width	19 in / 48.26 cm
Package 1 Length	33 in / 83.82 cm
Package 1 Height	38 in / 96.52 cm

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com

