



## **Double Girder Wire Rope Hoist 30 tons M5 class Service**

## **Key features**

- Duty Classification H4/M5/2m/Class D
- US and EU Standards ASME HST-4, ASME B30.16, IEC60204-32
- 3 Year Warranty, Customer Support and Service in the USA

## **Electric Wire Rope Hoist Description**

Our 30 tons M5 class service have a compact structure, light weight but high strength, precise positioning to improve the working efficiency. Modular design and multiple options can meet various demands of customers. High quality mechanical & electronic components can ensure good working performance. Low operation cost, green energy and environment friendly. Safe and reliable, running monitoring simple and convenient maintenance with high production efficiency improved by precise positioning.





## **Technical Specifications**

Rated Load Capacity	30 t	Hoist Motor Power	Sew Eurodrive
Standard Lifting Height	30 ft / 9 m	Hoist Reducer	Sew Eurodrive FA
Speed /min	0.8 - 3.2 m/min	Contactor	Schneider
Number of Speeds	2 Speed	Transmission / Reducer Type	Sew Eurodrive
Voltage	3 Phase 380/440~480V 50/60Hz	Humidity	<85%
<b>Total Power Watts</b>	38 kw	Temperature	-4°~104° F / -20°~40° C
Duty Class	H4/M5/2m/Class D	Trolley Power	1.5 kw x 2
Insulation Grade	F	Noise Level	82 dB
IEC Motor Protection	IP55	Trolley Speed /min	16 ~ 65 ft/min. / 5 ~ 20 m/min
IEC Electric Control Box Protection	IP65	Standards Compliance	ASME HST-4 , ASME B30.16 , B30.17 , EN14492-2 , EN60204-32
Control Voltage	48V	Warranty	3 Year