



# 2 ton Electric Chain Hoist w/ Power Trolley Variable Speed 380V 3ø 50~60HZ 20ft G100 Nickel Duty H4/M5

#### **Key features**

- Load Capacity: 2 tons (4,000 lbs) Designed for lifting medium to heavy loads.
- Voltage: 380V Standard voltage for industrial settings, suitable for high-power applications.
- Speed: Variable Speed Allows for adjustable lifting speeds to accommodate different operational needs, enhancing control and precision.
- 3 Year Warranty, Customer Support and Service in the USA

#### **Electric Chain Hoist Description**

This 2-ton electric chain hoist features a power trolley with variable speed control for precise lifting and smooth horizontal movement. It operates on a 380V 3-phase 50~60Hz power supply, delivering reliable and adaptable performance for various industrial applications.

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001






### **Technical Specifications**

Rated Load Capacity	2 ton	Load Chain Type	G100 Nikel
Standard Lifting Height	20 ft / 6 m	Load Chain Size	10 mm
Speed (f/m) / min	ft @60Hz 0.8~6.8 mt @50Hz	Chain Falls	1
Number of Speeds	Variable Speed	Chain Length	20 ft (6 m)
Voltage	3 Phase 380V 50Hz	Humidity	20%~90%
Total Power Watts	4000	Temperature	-4 ~ 104° F / -20 ~ 40° C
Duty Class	H4/M5/2m/Class D	Trolley Power	500
IEC Motor Protection	IP55	Trolley Speed /min	5.9~47.23 ft @60Hz 1.5~12 mt @50Hz
Control	Pendant Control IP66 and Optional Wireless	Trolley Number of Speeds	Variable
Control Voltage	24V	Standards Compliance	ASME HST-1 , ASME B30.16 , B30.17 , EN60204-34
Emergency Stop	Yes	Warranty	3 Year
Transmission / Reducer Type	Spur gearbox		

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001







		Dimension (mm)												
Rated load (t)	Туре	Minimum distance from the bottom of the track to the bottom hook: H	A	L	В	D	E	I	М	N	К	L	т	R
1	PWRXT1-01	473	440		285	210	20	105	140					
2	PWRXT2-01	516	590	3500.	276	368	210	31	24	25	42	32	242	167
3	PWRXT3-01	600	681	5500	350	422	264	36	28	35	52	42	242	167
5	PWRXT5-02	645	681		350	478	307	43	30	34	59	48	242	167

### **Unit Weight & Dimensions**

## **Packaging Weight & Dimensions**

H Minimum Headroom	600	Package 1 Net Weight	184.8 lbs / 84 Kg
W Width	422	Package 2 Net Weight	100.1 lbs / 45 Kg

prowinch.com

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001





23 in / 58.42 cm

A Total Height	600	Package 1 Gross Weight	308 lbs / 140 Kg
J Hook Opening	52	Package 2 Gross Weight	110 lbs / 50 Kg
D Depth	600	Package 1 Length	30 in / 76.2 cm
Total Weight (w/out cable or Chain)	155	Package 2 Length	11 in / 27.94 cm
Total Unit Weight	284.9 lbs / 130 Kg	Package 1 Width	20 in / 50.8 cm
		Package 2 Width	14 in / 35.56 cm
		Package 1 Height	31 in / 78.74 cm

Package 2 Height

prowinch.com

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001

