



5 Tons Scrapper Winch Explosion Proof Hydraulic Actuator - ATEX

Key features

- Load Capacity: Handles up to 5 tons, designed for heavy-duty scrapping and lifting applications.
- Explosion Proof: ATEX certified for use in hazardous environments with flammable gases or dust, ensuring safety in explosive atmospheres.
- Safety Features: Includes essential safety mechanisms such as overload protection, hydraulic control systems, and explosion-proof design to ensure secure and safe operation.
- 3 Year Warranty, Customer Support and Service in the USA

Winch Description

Ensure safety and reliability with our 5-ton scrapper winch featuring an explosion-proof hydraulic actuator, certified for ATEX compliance. Designed for hazardous environments, this winch combines powerful performance with advanced safety features to handle tough industrial tasks efficiently. The explosion-proof design protects against ignitions in explosive atmospheres, making it the ideal choice for high-risk applications.

Prowinch Scraper 5 Ton Winch

Our Scraper Winches are designed to get the best price, quality and performance ratio, backed by a 3-year warranty. The key components of the equipment are constantly tested and improved through our internal design processes, based on continuous improvement, under ISO9001: 2015 certification.

Performance and Quality

Suitable for use in transporting crushed material resulting from mining, in underground locations, in horizontal areas or on inclined planes with up to 45° slope.

Components

Assembled with the best components on the market that guarantee optimal equipment operation. Two-drum electrical equipment, powered by an advanced technology control board.





Technical Specifications

| 1st Layer Rated Capacity | 5 ton | IEC Electric Control Box Protection | IP65 |
|--------------------------|-----------------------------------|-------------------------------------|----------------------|
| Number of Speeds | 1 Speed - Optional Variable Speed | Control Voltage | 24V |
| Voltage | 3 Phase 380/440~480V 50/60Hz | Warranty | 3 Year |
| Motor Type (68) | Electric AC | Standard Lifting Height | Up to 492 ft / 150 m |
| IEC Motor Protection | IP55 | | |

Unit Weight & Dimensions

Packaging Weight & Dimensions

| Total Unit Weight | 5358 lbs / 2432 Kg | Package 1 Net Weight | 5358 lbs / 2431 Kg |
|-------------------|--------------------|------------------------|--------------------|
| | | Package 1 Width | 84 in / 213.36 cm |
| | | Package 1 Gross Weight | 5358 lbs / 2431 Kg |
| | | Package 1 Height | 35 in / 88.9 cm |
| | | Package 1 Length | 41 in / 104.14 cm |