



# 3300 lbs. 1.5 ton 20 ft Manual Chain Hoist G80 Black Tempered Chain

### **Key features**

- Lifting Capacity: Supports loads up to 3300 lbs (1.5 tons), making it suitable for various lifting and pulling applications.
- Lifting Height: Provides a maximum lifting height of 20 feet, allowing for versatility in handling different loads.
- Robust Construction: Built from high-quality materials to withstand demanding conditions, ensuring long-lasting performance and durability.
- 3 Year Warranty, Customer Support and Service in the USA

#### **Manual Chain Hoist Description**

The 3300 lbs (1.5 ton) Manual Chain Hoist is a reliable and efficient lifting tool designed for medium-duty applications. With a generous lifting height of 20 feet and constructed from high-quality G80 black tempered chain, this hoist is perfect for a variety of lifting tasks across different environments.

#### **Prowinch Manual Chain Hoist**

All of our **Manual Chain Hoists** are created with the goal of offering the best price-performance ratio. Key components such as lifespan factors are constantly tested and improved in order to offer the best product for the price.

#### Braking System

The reliable double pawl brake system is tested at 125% of the hoist capacity.

prowinch.com

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001





# **Technical Specifications**

Rated Load Capacity	3300 lb / 1500 kg	Load Chain Size	7x22 mm
Standard Lifting Height	10 ft / 3 m	Standards Compliance	ANSI/ASME B30.16, EN13157, ISO 16877-2008
Load Chain Type	G80	Warranty	3 Year

prowinch.com

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001




## **PWTB150-20F**


# **Prol/INCH**


Model/Modelo	PWTB050	PWTB100	PWTB150	PWTB200	PWTB300	PWTB500	PWTB1000	PWTB2000
A	4.9 in / 124 mm	5.3 in / 134 mm	5.9 in / 149 mm	6.2 in / 1	.57 mm	7.1 in /	180 mm	8.9 in / 226 mm
В	5.1 in / 129 mm	6.1 in / 154 mm	6.8 in / 172 mm	7.3 in / 185.42 mm	9.3 in / 236 mm	10.3 in / 261 mm	14.4 in / 365 mm	21.7 in / 551 mm
С	1.7 in / 43 mm	2.0 in / 50 mm	2.5 in /	63.5 mm	3.9 in / 99 mm	5.0 in / 127 mm	10.2 in / 259 mm	11.3 in / 287 mm
D	1.0 in / 25 mm	1.2 in / 30 mm	1.3 in ,	′ 33 mm	2.2 in / 55 mm	2.9 in / 73 mm	3.9 in / 99 mm	4.8 in / 121 mm
E	1.1 in / 27 mm	1.3 in /	33 mm	1.5 in / 38 mm	1.7 in / 43 mm	2.0 in / 50 mm	2.5 in / 63 mm	3.2 in / 81 mm
F	1.3 in / 33 mm	1.6 in / 40 mm	1.7 in / 43 mm	1.8 in / 45 mm	2.0 in / 50 mm	2.4 in / 60 mm	3.3 in / 83 mm	4.3 in / 109 mm
G	1.4 in / 35 mm	1.8 in / 45 mm	1.9 in / 48 mm	2.0 in / 50 mm	2.5 in / 63 mm	3.1 in / 78 mm		

3 t & 5 t


## 0.5 t, 1 t, 1.5 t & 2 t









30 t







prowinch.com

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001





## **Unit Weight & Dimensions**

H Minimum Headroom Total Unit Weight 1.2 ft / 0.3 m 33 lbs / 15 Kg

# **Packaging Weight & Dimensions**

Package 1 Net Weight	33 lbs / 15 Kg
Package 1 Width	6 in / 15.24 cm
Package 1 Gross Weight	35 lbs / 16 Kg
Package 1 Height	10 in / 25.4 cm
Package 1 Length	9 in / 22.86 cm

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001

