



Nylon+Aluminium Rod Energy Chain Inside H*W=47*304mm Outside H*W=79*345mm (Price per meter)

Key features

- Inside Dimensions: 47 mm height x 304 mm width
- Material Composition: Constructed from durable nylon and reinforced with aluminium rods for enhanced strength and reduced weight.
- Versatile Applications: Suitable for various machinery, robotics, and automated systems in industrial settings.
- 1 Year Warranty, Customer Support and Service in the USA

Nylon Aluminium Rod Energy Chain Inside Description

The Nylon Aluminium Rod Energy Chain features inside dimensions of 47 mm x 304 mm and outside dimensions of 79 mm x 345 mm. This combination of materials provides a lightweight yet robust solution for efficient cable management in demanding industrial applications.

Technical Specifications

| | | | |
|------------------------------------|-------------------------|-----------------------------|--|
| Warranty | 1 Year | Material | Engineering grade self lubricating Nylon (PA66) & Aluminum support RodsEng |
| Chain Internal Height x Width (mm) | 47 x 100 | Operating Temperature Range | -22°C to 110°C |
| Standard Bending Radius (mm) | 150 | Outdoor Usage | Yes |
| Bending Radius upon Request (mm) | 150, 200, 250, 280, 400 | Net Weight x meter | 5.00 kg |
| Chain External Height x Width (mm) | 79 x 141 | Gross Weight x meter | 5.40 Kg |
| Chain Pitch (mm) | 80 | | |

Unit Weight & Dimensions

| | | | |
|-------------------|------------------|------------------------|------------------|
| Total Unit Weight | 16.02 lbs / 8 Kg | Package 1 Net Weight | 11.02 lbs / 5 Kg |
| | | Package 1 Gross Weight | 11.90 lbs / 5 Kg |

Packaging Weight & Dimensions