



220 lbs. Manual Winch Automatic Brake

Key features

• 1 Year Warranty, Customer Support and Service in the USA

220 lbs. Manual Winch with Automatic Brake: Secure load handling, easy control, and enhanced safety for lifting and pulling tasks.





Technical Specifications

1st Layer Rated Capacity	220 lb / 100 kg	Gear Ratio	1:1
Duty Class	100% Duty Cycle	Recommended Wire Rope	ø13/64 in ø5 mm
Motor/Engine Type	Manual	Warranty	1 Year

Model/Modelo	PWUL100	PWUL300	PWUL500	PWUL1000	PWUL2000	PWUL3000
Required Effort 1st Rope Layer	25.35 lb / 11.5 kg	24.25 lb / 11 kg	26.45 lb / 12 kg		28.66 lb / 13 kg	39.68 lb / 18 kg
Esfuerzo requerido 1a capa de cable	23.33 to / 11.3 kg 24.23 to / 11 kg		20.43 lb / 12 kg		28.00 lb / 13 kg	33.00 ib / 10 kg
Drum Capacity	98.42 ft / 30 m		131.23 ft / 40 m			
Capacidad del Tambor						
Drum Diameter	1.88 in / 48 mm 2.38		/ 60.5 mm 3 in / 76.3 mm		3.50 in / 89.1 mm	4 in / 101.6 mm
Diámetro del tambor	1.00 111 / 40 111111	2.36 111 /	2.38 in / 60.5 mm		3.30 111 / 69.1 111111	4 111 / 101.6 111111
Can Wind per Turn	6.55 in / 166.5 mm	2.86 in / 72.8 mm	1.90 in / 48.4 mm	0.84 in / 21.7 mm	0.53 in / 13.6 mm	0.70 in / 18 mm
Capacidad de enrollar por giro	0.55 117 100.5 11111					
Reduction Gear Ratio	1:1	2.88:1	4.33:1	12.19:1	22.68:1	22.16:1
Relación de engranaje de reduccion	1.1					
Length of Lever Handle	9.44 in / 240 mm		13.77 in / 350 mm			
Dimensión de la palanca	J.44 III / 240 IIIIII		13.77 1117 330 111111			

Unit Weight & Dimensions

Packaging Weight & Dimensions

Total Unit Weight	15 lbs / 7 Kg	Package 1 Net Weight	15 lbs / 7 Kg
		Package 1 Width	7 in / 17.78 cm
		Package 1 Gross Weight	17 lbs / 8 Kg
		Package 1 Height	7 in / 17.78 cm
		Package 1 Length	12 in / 30.48 cm