



## 1100 lbs Manual Winch Automatic Brake

### Key features

- 1 Year Warranty, Customer Support and Service in the USA

1100 lbs Manual Winch Automatic Brake

## Technical Specifications

<b>1st Layer Rated Capacity</b>	1102 lb / 500 kg	<b>Gear Ratio</b>	4.33:1
<b>Duty Class</b>	100% Duty Cycle	<b>Recommended Wire Rope</b>	ø1/4 in   ø6.3 mm
<b>Motor/Engine Type</b>	Manual	<b>Warranty</b>	1 Year

Model/Modelo	PWUL100	PWUL300	PWUL500	PWUL1000	PWUL2000	PWUL3000
<b>Required Effort 1st Rope Layer</b> Esfuerzo requerido 1a capa de cable	25.35 lb / 11.5 kg	24.25 lb / 11 kg	26.45 lb / 12 kg		28.66 lb / 13 kg	39.68 lb / 18 kg
<b>Drum Capacity</b> Capacidad del Tambor	98.42 ft / 30 m		131.23 ft / 40 m			
<b>Drum Diameter</b> Diámetro del tambor	1.88 in / 48 mm	2.38 in / 60.5 mm	3 in / 76.3 mm	3.50 in / 89.1 mm	4 in / 101.6 mm	
<b>Can Wind per Turn</b> Capacidad de enrollar por giro	6.55 in / 166.5 mm	2.86 in / 72.8 mm	1.90 in / 48.4 mm	0.84 in / 21.7 mm	0.53 in / 13.6 mm	0.70 in / 18 mm
<b>Reduction Gear Ratio</b> Relación de engranaje de reduccion	1:1	2.88:1	4.33:1	12.19:1	22.68:1	22.16:1
<b>Length of Lever Handle</b> Dimensión de la palanca	9.44 in / 240 mm	13.77 in / 350 mm				

## Unit Weight & Dimensions

<b>Total Unit Weight</b>	28 lbs / 13 Kg	<b>Package 1 Net Weight</b>	28 lbs / 13 Kg
		<b>Package 1 Width</b>	11 in / 27.94 cm
		<b>Package 1 Gross Weight</b>	30 lbs / 14 Kg
		<b>Package 1 Height</b>	9 in / 22.86 cm
		<b>Package 1 Length</b>	15 in / 38.1 cm

## Packaging Weight & Dimensions