



## 4T x 6m Flat webbing sling Safety Factor 6:1

### Key features

- 3 Year Warranty, Customer Support and Service in the USA

4T x 6m Flat webbing sling Safety Factor 6:1

## Technical Specifications



Item No. 5 / Artículo 5	Working load limit/ Limite Carga de Trabajo	Width / Ancho			Color	Working Load at Different Model / Carga de trabajo en Diferentes Modelos					Standard / Estandar: EN1492-1	
		5:1	6:1	7:1		Straight / Vertical		Basket Lift / En U	7°-45°	Choker Hitch / Enlazada		45°-60°
												
PWWF	2204 lb / 1000 kg	0.98 in / 25 mm	1.18 in / 30 mm	Violet / Violeta	2204 lb / 1000 kg	4409 lb / 2000 kg	30864 lb / 1400 kg	1763 lb / 800 kg	2204 lb / 1000 kg			
	4409 lb / 2000 kg	1.96 in / 50 mm	2.36 in / 60 mm	Green / Verde	4409 lb / 2000 kg	8818 lb / 4000 kg	6172 lb / 2800 kg	3527 lb / 1600 kg	4409 lb / 2000 kg			
	6613 lb / 3000 kg	2.95 in / 75 mm	3.54 in / 90 mm	Yellow / Amarillo	6613 lb / 3000 kg	13227 lb / 6000 kg	9259 lb / 4200 kg	5291 lb / 2400 kg	6613 lb / 3000 kg			
	8818 lb / 4000 kg	3.93 in / 100 mm	4.72 in / 120 mm	Grey / Gris	8818 lb / 4000 kg	17636 lb / 8000 kg	12345 lb / 5600 kg	7054 lb / 3200 kg	8818 lb / 4000 kg			
	11023 lb / 5000 kg	4.92 / 125 mm	5.90 in / 150 mm	Red / Rojo	11023 lb / 5000 kg	22046 lb / 10000 kg	15432 lb / 7000 kg	8818 lb / 4000 kg	11023 lb / 5000 kg			
	13227 lb / 6000 kg	5.90 in / 150 mm	7.08 in / 180 mm	Brown / Marrón	13227 lb / 6000 kg	26455 lb / 12000 kg	18518 lb / 8400 kg	10582 lb / 4800 kg	13227 lb / 6000 kg			
	17636 lb / 8000 kg	7.87 in / 200 mm	9.44 in / 240 mm	Blue / Azul	17636 lb / 8000 kg	35273 lb / 16000 kg	24691 lb / 11200 kg	14109 lb / 6400 kg	17636 lb / 8000 kg			
	22046 lb / 10000 kg	9.84 in / 250 mm	11.8 in / 300 mm	Orange / Naranja	22046 lb / 10000 kg	44092 lb / 20000 kg	30864 lb / 14000 kg	17636 lb / 8000 kg	22046 lb / 10000 kg			
	26455 lb / 12000 kg	11.8 in / 300 mm			26455 lb / 12000 kg	52910 lb / 24000 kg	37037 lb / 16800 kg	21164 lb / 9600 kg	26455 lb / 12000 kg			

## Unit Weight & Dimensions

Total Unit Weight

6 lbs / 3 Kg