

## 8T x 6m Flat webbing sling Safety Factor 6:1

### Key features

- 3 Year Warranty, Customer Support and Service in the USA



8T x 6m Flat webbing sling Safety Factor 6:1

Technical Specifications



| Item No. 5 /<br>Artículo 5 | Working load limit/<br>Limite Carga de Trabajo | Width / Ancho    |                  |                   | Color               | Working Load at Different Model / Carga de trabajo en Diferentes Modelos          |   |   |   |   | Standard /<br>Estandar:<br>EN1492-1 |         |
|----------------------------|--|------------------|------------------|-------------------|---------------------|---|---|---|---|---|-------------------------------------|---------|
|                            |  | 5:1              | 6:1              | 7:1               |                     | Straight / Vertical   |   | Basket Lift / En U  | 7°-45°  | Choker Hitch / Enlazada   |                                     | 45°-60° |
|                            |  |                  |                  |                   |                     |  |  |  |  |  |                                     |         |
| PWWF                       | 2204 lb / 1000 kg                              | 0.98 in / 25 mm  | 1.18 in / 30 mm  | Violet / Violeta  | 2204 lb / 1000 kg   | 4409 lb / 2000 kg   | 30864 lb / 1400 kg  | 1763 lb / 800 kg  | 2204 lb / 1000 kg   |   |                                     |         |
|                            | 4409 lb / 2000 kg                              | 1.96 in / 50 mm  | 2.36 in / 60 mm  | Green / Verde     | 4409 lb / 2000 kg   | 8818 lb / 4000 kg   | 6172 lb / 2800 kg   | 3527 lb / 1600 kg   | 4409 lb / 2000 kg   |   |                                     |         |
|                            | 6613 lb / 3000 kg                              | 2.95 in / 75 mm  | 3.54 in / 90 mm  | Yellow / Amarillo | 6613 lb / 3000 kg   | 13227 lb / 6000 kg  | 9259 lb / 4200 kg   | 5291 lb / 2400 kg   | 6613 lb / 3000 kg   |   |                                     |         |
|                            | 8818 lb / 4000 kg                              | 3.93 in / 100 mm | 4.72 in / 120 mm | Grey / Gris       | 8818 lb / 4000 kg   | 17636 lb / 8000 kg  | 12345 lb / 5600 kg  | 7054 lb / 3200 kg   | 8818 lb / 4000 kg   |   |                                     |         |
|                            | 11023 lb / 5000 kg                             | 4.92 / 125 mm    | 5.90 in / 150 mm | Red / Rojo        | 11023 lb / 5000 kg  | 22046 lb / 10000 kg   | 15432 lb / 7000 kg  | 8818 lb / 4000 kg   | 11023 lb / 5000 kg  |   |                                     |         |
|                            | 13227 lb / 6000 kg                             | 5.90 in / 150 mm | 7.08 in / 180 mm | Brown / Marrón    | 13227 lb / 6000 kg  | 26455 lb / 12000 kg   | 18518 lb / 8400 kg  | 10582 lb / 4800 kg  | 13227 lb / 6000 kg  |   |                                     |         |
|                            | 17636 lb / 8000 kg                             | 7.87 in / 200 mm | 9.44 in / 240 mm | Blue / Azul       | 17636 lb / 8000 kg  | 35273 lb / 16000 kg   | 24691 lb / 11200 kg   | 14109 lb / 6400 kg  | 17636 lb / 8000 kg  |   |                                     |         |
|                            | 22046 lb / 10000 kg                            | 9.84 in / 250 mm | 11.8 in / 300 mm | Orange / Naranja  | 22046 lb / 10000 kg | 44092 lb / 20000 kg   | 30864 lb / 14000 kg   | 17636 lb / 8000 kg  | 22046 lb / 10000 kg   |   |                                     |         |
|                            | 26455 lb / 12000 kg                            | 11.8 in / 300 mm |                  |                   | 26455 lb / 12000 kg | 52910 lb / 24000 kg   | 37037 lb / 16800 kg   | 21164 lb / 9600 kg  | 26455 lb / 12000 kg   |   |                                     |         |

Unit Weight & Dimensions

|                   |               |
|-------------------|---------------|
| Total Unit Weight | 15 lbs / 7 Kg |
|-------------------|---------------|