



6T x 6m Endless Round Sling Safety Factor 6:1

Key features

- 3 Year Warranty, Customer Support and Service in the USA

6T x 6m Endless Round Sling Safety Factor 6:1

Technical Specifications



Item No. 5 / Artículo 5	Working load limit/ Limite Carga de Trabajo	Width/Ancho	Color	Working Load at Different Model / Carga de trabajo en Diferentes Modelos					Standard / Estandar: EN1492-1
		7:1		Straight / Vertical	Basket Lift / En "U"	7°-45°	Choker Hitch / Enlazada	45°-60°	
PWWR	2204 lb / 1000 kg	1.77 in / 45 mm	Violet / Violeta						
	4409 lb / 2000 kg	1.85 in / 47 mm	Green / Verde	2204 lb / 1000 kg	4409 lb / 2000 kg	30864 lb / 1400 kg	1763 lb / 800 kg	2204 lb / 1000 kg	
	6613 lb / 3000 kg	2.28 in / 58 mm	Yellow / Amarillo	4409 lb / 2000 kg	8818 lb / 4000 kg	6172 lb / 2800 kg	3527 lb / 1600 kg	4409 lb / 2000 kg	
	8818 lb / 4000 kg	2.83 in / 72 mm	Grey / Gris	6613 lb / 3000 kg	13227 lb / 6000 kg	9259 lb / 4200 kg	5291 lb / 2400 kg	6613 lb / 3000 kg	
	11023 lb / 5000 kg	3.26 in / 83 mm	Red / Rojo	8818 lb / 4000 kg	17636 lb / 8000 kg	12345 lb / 5600 kg	7054 lb / 3200 kg	8818 lb / 4000 kg	
	13227 lb / 6000 kg	3.54 in / 90 mm	Brown / Marrón	11023 lb / 5000 kg	22046 lb / 10000 kg	15432 lb / 7000 kg	8818 lb / 4000 kg	11023 lb / 5000 kg	
	17636 lb / 8000 kg	4.01 in / 102 mm	Blue / Azul	13227 lb / 6000 kg	26455 lb / 12000 kg	18518 lb / 8400 kg	10582 lb / 4800 kg	13227 lb / 6000 kg	
	22046 lb / 10000 kg	4.56 in / 116 mm	Orange / Naranja	17636 lb / 8000 kg	35273 lb / 16000 kg	24691 lb / 11200 kg	14109 lb / 6400 kg	17636 lb / 8000 kg	
	26455 lb / 12000 kg			22046 lb / 10000 kg	44092 lb / 20000 kg	30864 lb / 14000 kg	17636 lb / 8000 kg	22046 lb / 10000 kg	
				26455 lb / 12000 kg	52910 lb / 24000 kg	37037 lb / 16800 kg	21164 lb / 9600 kg	26455 lb / 12000 kg	

Unit Weight & Dimensions

Total Unit Weight

13 lbs / 6 Kg